

THERMOSTATIC GAS GRIDDLES



Features

- All models can be operated using natural or LP gas (conversion kit included).
- Unlike manual griddles that only have temperature ranges, thermostatic griddles can be set to an exact temperature, and will maintain that temperature within a couple of degrees.
- 1 inch (2.5 cm) griddle plate thickness for better heat retention, faster recovery, and more even heat distribution than thin plates.
- Heavy-duty stainless steel full-cooking depth dual-ported burners for long life and easy maintenance.
- Manually controlled, independent cooking zones.
- Throttling thermostat and U-shaped burner every 12" for exceptional control.
- Four countertop units available with 15", 24", 36", and 48" widths (37.7cm, 61cm, 91.1 cm, and 121.6 cm) and 20" depth (50.8 cm).



Models & Dimensions



Thermostatic Gas Griddles



model CE-G24TPF represented measurements in inches [cm]

Specifications

| Model | Cooking Surface (W x D) | No. of Burners | BTUs per Hour | Product Dimensions (H x W x D) | Ship Dimensions (H x W x D) | Ship Weight |
|-------------------------------|-----------------------------------|-------------------|---------------------|--|---|-------------------------|
| CE-G15TPF (6602-10000) | 15" x 20" (37.7 cm x 50.8 cm) | 1 | 30,000 | 15.6" x 15" x 30" (39.6 cm x 38.1 cm x 76.2 cm) | 19.1" x 18.5" x 32.5" (47 cm x 82.6 cm x 48.5 cm) | 165 lbs. (74.8 kg.) |
| CE-G24TPF (6602-10001) | 24" x 20" (61 cm x 50.8 cm) | 2 | 60,000 | 15.6" x 24" x 30" (39.6 cm x 61 cm x 76.2 cm) | 19.1" x 28" x 32.5" (71.1 cm x 82.6 cm x 48.5 cm) | 210 lbs. (95.3 kg.) |
| CE-G36TPF (6602-10002) | 36" x 20" (91.1 cm x 50.8 cm) | 3 | 90,000 | 15.6" x 36" x 30" (39.6 cm x 91 cm x 76.2 cm) | 19.1" x 40" x 32.5" (101.6 cm x 82.6 cm x 48.5 cm) | 345 lbs. (156.5 kg.) |
| CE-G48TPF (6602-10003) | 48" x 20" (121.6 cm x 50.8 cm) | 4 | 120,000 | 15.6″ x 48″ x 30″ (39.6 cm x 122 cm x 76.2 cm) | 18" x 52" x 32.5" (132.1 cm x 82.6 cm x 48.5 cm) | 360 lbs. (163.3 kg.) |



Grindmaster-Cecilware™ 4003 Collins Lane, Louisville, KY 40245 USA

Tel: +1.502.425.4776 / 800.695.4500 (USA & Canada only) • Fax: +1.502.425.4664 • www.gmcw.com • Email: info@gmcw.com