

GRINDMASTER

UNIC

Crathco

PRODUCT CATALOG



TABLE OF CONTENTS

BEVERAGE EQUIPMENT

Coffee Grinders	4
Water Purity	6
Coffee Brewers	9
Coffee Urns	24
Coffee Brew Basket & Coffee Filters	34
Iced Tea Brewers & Dispensers	36
Hot Tea Urns	38
Hot Water Heaters & Dispensers	39
Powdered Beverage Dispensers	43
Heated Dispensers	46
Espresso Machines	47
Espresso Grinder Dosers	59
Orange Juice Machines	63
Cold Beverage Dispensers	64
Frozen Beverage Dispensers	72

WARMING EQUIPMENT

Warming & Heated Dispensers	94
-----------------------------	----

COOLING EQUIPMENT

Countertop Refrigerators	95
--------------------------	----

HELPFUL INFORMATION

Planned Maintenance	97
Product Certifications	101

COOKING EQUIPMENT

Fryers	82
Griddles	86
Charbroilers	89
Hot Plates	90
Panini Grills	91

* Images and photographs in this document may vary slightly from the actual delivered product and are not meant to be exact representations of the same.

* Product specifications are subject to improvement or change.

BEVERAGE EQUIPMENT



COFFEE GRINDERS

GRINDMASTER

RETAIL 800 Series







Compact and Powerful

Don't let their size fool you. The 800 series coffee grinders may seem unassuming with their space-saving size of only 7" - 8" wide. But these little guys use their fast grind speed and powerful, energy-efficient 0.5 hp motor to make quick work of coffee beans.

- Motor includes circuit breaker.
- Multiple grind particle profile selections.
- Ideal for low to medium volume specialty shops, grocery stores, doughnut shops, and c-stores.
- Precision burrs guaranteed to process 40,000 lbs. of coffee at medium grind.
- Exceptional warranty program: burrs - 4 years or 40,000 lbs. of coffee, all other components - 2 years.

Please see our complete line of espresso grinders from page 59.



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	810S (810-BS)	Black with 1.5 lbs. hopper	22" x 7" x 14"
	835S (835-BS)	Black with 1.5 lbs. hopper	22" x 7" x 15"
	875S (875-BS)	Black with 3 lbs. hopper	28" x 7" x 15"
	875S (875-RS)	Red with 3 lbs. hopper	28" x 7" x 15"
	890BS (890-BS)	Black with European slicing burrs for precision grinding and 3 lbs. hopper	28" x 7" x 15"
	890T (890-B-T)	Black with European slicing burrs for precision grinding and 5 lbs. hopper. <i>Does not include base or tray. Must be bolted to counter.</i>	31.25" x 7.5" x 14"

GROUND COFFEE DISPENSER


GRINDMASTER

DISPENSERS Ground Coffee Dispenser

Dispense perfect portions of ground coffee into your brew basket - every time! The Model A doesn't grind coffee, but provides carefully measured doses of ground coffee at the push of a button. Simplifies brewing, and guarantees consistency.

- No mess, waste, or bridging.
- Stainless steel construction.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 Model A (078650L)	Dispenses directly into a brew basket up to 8.75" in diameter	19.5" x 9.25" x 11.25"

WATER FILTER KIT

GRINDMASTER

Purity C500 Water Filter Starter Kit


Start Here for Great Water

The complete kit to test and produce clearer, cleaner, great tasting water. Begin with the included water hardness testing kit, and then set the adjustable bypass from 0 to 70% to produce exactly the water you need - minimizing scale, and retaining minerals that benefit taste.

Four-step filtration for clearer, cleaner, great tasting water:

1. Prefiltration: Removes coarse particles.
 2. Temporary Hardness Reduction: A hydrogen ion exchanger reduces the temporary hardness content and prevents scale deposits.
 3. Activated Carbon Filtration: Improves taste and odor.
 4. Fine Filtration: Retains small particles.
- Reduces hardness, alkalinity, and TDS.
 - Prevents limescale deposits in equipment.
 - Removes particulates, along with metal ions, such as lead or copper.
 - Eliminates impurities like chlorine that affect the taste, aroma, and quality of water.
 - Decreases service and repair costs.
 - All of the water — including the bypass water — runs through an activated carbon filter, resulting in the removal of substances that have an adverse effect on the taste and aroma.
 - Decarbonation filter with weak acid cation (WAC) resins replace the hardness minerals (calcium and magnesium ions) with hydrogen ions for a saltless softening.
 - Easy-to-use Locking System - remove and replace the filter cartridge quickly and easily.
 - Chlorine reduction: minimum removal of 85.2%, average removal of 88.6%.
 - Operates in horizontal or vertical position.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 250-00011	Includes filter, water hardness test kit, and filter head with variable bypass adjustable to local water conditions. Plumbing: 3/8" 18 NPT connections. Maximum operating pressure of 8.6 bar/125 psi.	Filter head and cartridge: 22" x 6" x 6"

Optional Replacement Filter

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
250-00012	Replacement Filter Cartridge for Purity C500 water filter	6.5" x 6.5" x 23.25"

WATER FILTER SYSTEM

GRINDMASTER

Space Saving Water Filter System

Cover Your Basic Filtration at the Exact Point of Need

Get the benefits of both water softener and dual-purpose carbon filter in this single-mounting system. Convenient and compact, the water softener reduces hardness, mineral build-up, and scale deposits that can damage your machine, while the dual-action carbon filter removes impurities such as fine sediment, dirt, rust, THMs, VOCs, and pesticides, and reduces impurities like chlorine that affect the taste, aroma, and quality of water.

- Mounted in series, for installations where space is limited.
- Pressure-relief button on the inlet side relieves housing pressure during cartridge changes.

Water Softener Filter

Designed to allow optimal contact between water and bed of FDA-grade softener resin, ensuring maximum ion exchange.

- Flow Rate: 0.5 gpm
- Temperature Rating: 40°F -100°F

Dual-purpose Carbon Filter

Extremely fine filter protects against impurities down to 5 microns nominal, which removes THMs, VOCs, and pesticides.

- Flow Rate: Maximum flow rate of 2,500 gallons @ 2.5 gpm
- Temperature Rating: 40°F - 125°F



Note: This filtration system cannot be used with twin 1.5 gallon coffee brewers.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
60206	Filter System Includes carbon filter cartridge, water softener cartridge, and (2) 10" low-profile polypropylene housings, plumbed together for easier installation. Mounted with white powder-coated carbon steel wall-mounting bracket. Maximum Pressure: 125 psi Maximum Operating Room Temperature: 100°F	14" x 10.5" x 5.25"

Optional Replacement Cartridges

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
60253	Replacement Water Softener Cartridge Design allows optimal contact between water and bed of FDA-grade softener resin, ensuring maximum ion exchange. Filter Media: Cation, sodium-form resin beads, 20 x 40 mesh, R-SO3-Na+ Capacity: 750 grains CaCO ₃ Flow Rate: 0.5 gpm	6.5" x 6.5" x 23.25"
60254	Replacement Carbon Filter Cartridge Cartridges of a carbon-impregnated cellulose media Protects against sediment down to 5 microns nominal Capacity: >5,000 gallons Chlorine Taste & Odor Reduction @ 1 gpm	9.75" x 2.88" diameter

WATER FILTER SYSTEM

GRINDMASTER

Water Filter System for RC400 Single Cup Brewers

Water Softening and Scale Protection

Effectively filters dirt, extra-fine particles, and cloudiness, and reduces limescale, and chlorine taste and odor.

- Provides 5 Micron Water Filtration
- Treatment of hardness up to 6 Grains Per Gallon
- Flow Rate: 1.5 gpm
- Temperature Rating: 35°F -100°F
- Capacity: 3,000 gallons
- Working Pressure: 10 - 125 psi
- Great RO pre-filtration



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
250-00034	Water filter kit contains all needed hardware and filter for application to the RC400 Single Cup brewer	12" x 4" x 4"

WATER PUMP KIT

GRINDMASTER

External Bottled Water Pump Kit

Provides Water Wherever You Are!

For remote locations where a water supply is inaccessible, this portable and compact point-of-use pump dispenses purified water from five gallon bottles.

- Quick-connect ports allow assembly of system and connection in seconds.
- Built-in back-flow prevention.
- Long-life motor ensures years of reliable operation.
- Illuminated on/off switch provides clear visibility.
- Quiet operation with noise-dampening rubber feet.
- Thermal overload protection prevents overheating.
- Auto shut-off when the water source is depleted and restarts when water is restored.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
63174	Includes main module with on/off rocker switch, single-inlet suction wand and hose assembly with universal seal cap, 20 feet of 0.25" discharge tubing, fittings kit, wall power transformer	Control Box: 3" x 5.1" x 7.6" Suction Wand: 23" length (4" extends past the top of the bottle)

COFFEE BREWERS

GRINDMASTER

RC400 Single Serve Coffee Brewers

Authentic Flavors of the World, One Cup at a Time

Brew great tasting single serve beverages with the stylish, powerful, and easy-to-use RC400. Compatible for use with any single-serve capsule, including RealCup™ and K-Cup®. Pulse brew and pre-infusion are optimized for coffee, tea, and cocoa, and the patent-pending brew chamber ensures even water distribution for full flavor every time.

- Plumbed in and pour-over capable right out of the box.
- 72 oz. cold water reservoir.
- Large touchscreen and easy-to-use one-touch controls.
- Digital control makes selection of beverage type and size simple.
- Faster brew with no lag time.
- More operator settings, including resettable brew count and customizable default options.
- Six brew size options from 4 oz to 16 oz. provide user with the selection of their choice.
- Adjustable platform for oversized travel mugs.
- Patented brew chamber ensures even water distribution for full flavor every time.
- Energy save mode engages at a programmed time of day, or when brewer has been inactive.
- Added safety with locking brew chamber.
- Commercial grade parts ensure a long life in heavy-usage locations.
- Repairable machine with available replacement parts.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
RC400 (0001-10000)	Single cup capsule brewer can be used as pourover or plumbed in. Plumbing: water pressure from 10-100 psi required	15.75" x 10.75" x 14.75"

Optional Water Filter for RC400*

MODEL	DESCRIPTION
250-00034	Water filter kit contains all needed hardware and filter for application to the RC400 Single Cup brewer

* RealCup™ brand has no affiliation with K-Cup® or Keurig, Inc. Keurig® and K-Cup® are registered trademarks of Keurig, Inc.

POUROVER COFFEE BREWERS

GRINDMASTER

Portable Pourover Coffee Brewers






Perfect Coffee. Will Travel.

This just may be the brewer you are looking for.
Adaptable. Flexible. Solid and Dependable.

Meet the Portable Pourover Family of Coffee Brewers. Stand-alone, temperature-controlled powerhouses that brew directly into decanters or airpots. Most models have additional warmers built-in, so you can keep extra decanters of coffee ready to be served.

- Completely portable unit.
- Convenient, easy operation for consistent, high-quality coffee.
- Just plug it in and go! Requires no plumbing.
- Simply pour in the water for a fresh, delicious pot of coffee.
- All stainless steel construction.
- 1.2 gallon tank capacity.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 CPO-1P-15A (0002-10001)	Warmers: 1 bottom NSF Sanitation, cNSFus Electrical Certification	17.5" x 8.25" x 17.75"
 CPO-2P-15A (0002-20001)	Warmers: 2 total: 1 top and 1 bottom NSF Sanitation, NSF Electrical Certification	18.5" x 8.25" x 17.75"
 CPO-3P-15A (0002-30001)	Warmers: 3 total: 2 top and 1 bottom NSF Sanitation, NSF Electrical Certification	18.5" x 8.25" x 17.75"
 CPO-3RP-15A (0002-30005)	Warmers: 3 total: 1 right top, 1 bottom, 1 right bottom NSF Sanitation, NSF Electrical Certification	17.5" x 16.5" x 17.75"
 CPO-SAPP (0002-00003)	No Warmers: Brews directly into airpot NSF Sanitation, cNSFus Electrical Certification	25" x 8.25" x 17.75"

Note: Decanters and airpots sold separately. See pages 20 - 21.

DIGITAL AIRPOT COFFEE BREWERS

GRINDMASTER

PrecisionBrew® Digital Airpot Brewers

Lasting Warmth

Digitally controlled with PrecisionBrew® Technology. The brewer holds the brew temperature to +/- 1° F during the complete brew cycle.

- Brews into airpots (sold separately).
- Airpots hold freshly brewed coffee for hours without additional heat.
- Pour-over capability – automatically converts to pour-over mode when the control system does not sense water.
- Low temp/no brew allows the brew cycle to begin only when the water has reached the optimum brew temperature.
- Energy-saving 'sleep mode' feature.
- Pulse brewing / pre-infusion allows the brew sequence to extract up to 20% more dissolved solids per batch of coffee.
- Programmable features include number of pulses, pulse-on time, and pulse-off time.
- Changing the pulse sequence does not affect the brew volume.
- Stainless steel brew basket.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
B-SAP (AB-SAP)	Single, digitally-controlled 2.2 L airpot brewer	25.25" x 8.25" x 17.75"

Note: Airpots sold separately. See page 21.

DIGITAL DECANTER COFFEE BREWERS



PrecisionBrew® Digital Decanter Brewers

Exact Temperature

Digitally controlled with PrecisionBrew® Technology. The brewer holds the brew temperature to +/- 1° F during the complete brew cycle.

- Brews into decanters (sold separately).
- Pourover capability – automatically converts to pourover mode when the control system does not sense water.
- Low temp/no brew allows the brew cycle to begin only when the water has reached the optimum brew temperature.
- Energy-saving ‘sleep mode’ feature.
- Stainless steel brew basket.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	B-3 (AB-3)	Warmers: 1 bottom, 2 top	19.25" x 8.25" x 17.75"
	B-3WL (AB-3WL)	Warmers: 1 bottom, 2 on the left side	17.75" x 16.25" x 17.75"
	B-3WR (AB-3WR)	Warmers: 1 bottom, 2 on the right side	17.75" x 16.25" x 17.75"

Note: Decanters sold separately. See page 20.

THERMAL GRAVITY POT COFFEE BREWERS

GRINDMASTER


PrecisionBrew® Thermal Gravity Container Brewers

Vacuum Fresh

Digitally controlled with PrecisionBrew® Technology. The brewer holds the brew temperature to $\pm 1^{\circ}\text{F}$ during the complete brew cycle.

- Brews into 2.5 L vacuum-insulated gravity containers (sold separately).
- Energy-saving 'sleep mode' feature.
- Low Temp/No Brew setting allows the brew cycle to begin only when the water has reached the optimum brew temperature.
- Pulse brewing / pre-infusion allows the brew sequence to extract up to 20% more dissolved solids per batch of coffee.
- Programmable number of pulses, pulse-on time, and pulse-off time.
- Changing the pulse sequence does not affect the brew volume.
- Stainless steel brew basket.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 B-SGP (AB-SGP)	Single, digitally controlled brewer	29" x 8.25" x 18.75"

Note: Gravity pot sold separately. See below.

Optional Gravity Containers



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 AGP-2.5 (AGP-2.5)	2.5 L vacuum-insulated gravity container for use with B-SGP. Portable and holds fresh coffee for hours without additional heat	17.5" x 8" x 9"

SHUTTLE® COFFEE BREWERS

GRINDMASTER

PrecisionBrew® Coffee Solutions



Touchscreen Digital Interface

The PrecisionBrew family of coffee brewers are all equipped with advanced touchscreen digital interfaces - 7" color displays with intuitive, icon-driven menus for brewing and operation. Multiple recipe selections, interactive diagnostics, programmed brewing, and attractive, eye-catching merchandising for your machine are all available through the straightforward, easy-to-understand interfaces, keeping the whole process smooth and easy.



Encapsulair™

The First-in-Industry technology Encapsulair found in the PrecisionBrew Air-heated models, uses the insulating power of air between its internal chambers to surround and protect your brewed coffee. The Encapsulair Shuttle maintains your coffee's temperature and flavor, giving you consistent quality and satisfied customers while reducing wasted beverages.



Java-tate™

The Java-tate feature gently stirs the coffee at regular, short intervals to keep undissolved particles in suspension, ensuring a consistent flavor profile from the first cup to the very last. Customers can see the blending through the clear sight glass on the front of the machine. Only available in Encapsulair shuttles.




Virtual Sight Glass

The backlit, internal sight glass in the Encapsulair shuttle provides an LED readiness and freshness indicator for the brew. The color changing light lets you know at a glance when the brew is complete, and when it is time to make more coffee. Plus, the internal placement of the sight glass means no cold-slugging of coffee, and no sight glass to clean!



Shuttle Sensors

Everything about the PrecisionBrew has been optimized to ensure health, safety, and easy operations. The sensor system will not allow brewing if the shuttle is not present or misaligned. Safety first!



Update via USB Drive

Every PrecisionBrew model is programmable locally on the machine, and updates can be made via USB. Eliminates the need to manually key in changes to every machine at every location requires less time in product start-up, travel, and management. Pre-programmed machines can also be transferred to different locations, ensuring a consistent process of brewing.

SHUTTLE® COFFEE BREWERS

GRINDMASTER

PrecisionBrew® Air-Heated Shuttle® Brewers

Maintain Delicious Flavor

Single and twin digital virtual sight glass models brew into 1.5 gallon air-heated Shuttle(s).

- Portable Encapsulair Shuttles insulate with air between the internal chambers, maintaining coffee temperature and flavor.
- Java-tate technology inside the shuttles gently stirs the brewed coffee at regular, short intervals, to keep undissolved particles in suspension, ensuring a consistent flavor profile from the first cup to the very last.
- The backlit, internal sight glass in the Encapsulair shuttle provides an LED readiness and freshness indicator for the brew. The color changing light lets you know at a glance when the brew is complete, and when it is time to make more coffee.
- The internal placement of the sight glass means no cold-slugging of coffee, and no sight glass to clean!
- Advanced touchscreen digital interface simplifies and streamlines brewing and operation.
- Shuttle safety sensors prevent brewing when server is not in place.
- Standard electronic basket lock prevents basket removal during brewing and dripout.
- 3.2 gallon heating tank per brew head.
- (3) independent brew volumes of 0.5, 1.0, 1.5 gallons let you be prepared for a busy morning rush and eliminate waste during slower sales periods.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 PBC-1A (1004-001)	Single digitally controlled brewer with virtual sight glass and compatible with Air -Heated Shuttle*	30.13" x 9.13" x 18.88"
 PBC-2A (1004-003)	Twin digitally controlled brewer with virtual sight glass and compatible with Air -Heated Shuttles*	30.13" x 18.13" x 18.88"

* Air Heated Shuttles sold separately.

Note: Shuttle graphics sold separately.

Note: Order ABB2.0WP filters. Accessories available separately.

Note: Unit does not ship with cord or plug. Please contact local qualified service agency for installation.

SHUTTLE® COFFEE BREWERS





PrecisionBrew® Warmer Shuttle® Brewers

Reimagined Brewing

Single and twin digital models brew into 1.5 gallon warmer Shuttle(s).

- Digitally controlled with PrecisionBrew Technology.
- Advanced touchscreen digital interface simplifies and streamlines brewing and operation.
- Troubleshoot with interactive diagnostics through touch display.
- Minimal training with icon-driven programming.
- Shuttle safety sensors prevent brewing when server is not in place.
- Standard electronic basket lock prevents basket removal during brewing and dripout.
- 3.2 gallon heating tank per brew head.
- (3) independent brew volumes of 0.5, 1.0, 1.5 gallons let you be prepared for a busy morning rush and eliminate waste during slower sales periods.
- With the twin model, you can brew two different beverages in side-by-side dispensers and expand your beverage offerings.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	PBC-1W (1004-002)	Single digitally controlled warmer shuttle brewer	30.13" x 9.13" x 18.88"
	PBC-2W (1004-004)	Twin digitally controlled warmer shuttle brewer	30.13" x 18.13" x 18.88"

Note: Warmer Shuttles sold separately.
Note: Shuttle graphics sold separately.
Note: Order ABB2.OWP filters. Accessories available separately.
Note: Unit does not ship with cord or plug. Please contact local qualified service agency for installation.

SHUTTLE® COFFEE BREWERS

GRINDMASTER





PrecisionBrew® Vacuum Shuttle® Brewers

The Choice is Yours

Single and twin models brew into 1.5 gallon vacuum Shuttle(s).

- Available with or without stand.
- Digitally controlled with PrecisionBrew Technology.
- Advanced touchscreen digital interface simplifies and streamlines brewing and operation.
- Troubleshoot with interactive diagnostics through touch display.
- Minimal training with icon-driven programming.
- (3) independent brew volumes of 0.5, 1.0, 1.5 gallons let you be prepared for a busy morning rush and eliminate waste during slower sales periods.
- With the twin model, you can brew two different beverages in side-by-side dispensers and expand your beverage offerings.
- Shuttle safety sensors prevent brewing when server is not in place.
- Standard electronic basket lock prevents basket removal during brewing and dripout.
- 3.2 gallon heating tank per brew head.



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	PBC-1V (1004-005)	Single digitally controlled brewer for use with vacuum shuttle without stand	33.56" x 9.13" x 19.13"
	PBC-2V (1004-006)	Twin digitally controlled brewer for use with vacuum shuttle without stands	33.56" x 18.13" x 19.13"
	PBC-1VS (1004-007)	Single digitally controlled brewer for use with vacuum shuttle with stand	35" x 12.3" x 19.13"
	PBC-2VS (1004-008)	Twin digitally controlled brewer for use with vacuum shuttle with stands	35" x 21.75" x 19.13"

Note: Vacuum Shuttles sold separately.

Note: Shuttle graphics sold separately.

Note: Order ABB2.0WP filters. Accessories available separately.

Note: Unit does not ship with cord or plug. Please contact local qualified service agency for installation.

SHUTTLES® COFFEE BREWERS

GRINDMASTER




PrecisionBrew® Shuttles® & Stands



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 AS15 (2503-006)	Air-heated Shuttle 1.5 gal.	12" x 9" x 14.38"
 VS15 (2503-002)	Vacuum Shuttle With Stand 1.5 gal.	24.38" x 8" x 12.81"
 V15 (2503-001)	Vacuum Shuttle Without Stand 1.5 gal.	15.88" x 8" x 12.75"
 WS15 (2503-007)	Warmer Shuttle 1.5 gal.	12" x 9" x 14.38"

PrecisionBrew® Shuttle Stands






MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 RAS1 (1502-004)	Air-heated Shuttle Stand	18" x 9.13" x 13"
 RWS1 (1503-004)	Warmer Shuttle Stand	7.5" x 9.13" x 9.25"
 VSS (2503-003)	Vacuum Shuttle Stand	9.375 x 8 x 12.75

GRAPHICS & ACCESSORIES

GRINDMASTER




PrecisionBrew®

Optional Shuttle Graphics

MODEL		DESCRIPTION
	380-00335	Air-heated Shuttle Graphics
	380-00439	Vacuum Shuttle Graphics
	380-00336	Warmer Shuttle Graphics

Brew Baskets and Filters



MODEL		DESCRIPTION
	230-00173	Stainless Steel Brew Basket
	230-00199	Plastic Brew Basket
	ABB2.0WP	14" bottom, 6" sidewall filter paper, 500 per box

ACCESSORIES

GRINDMASTER

Coffee Decanters

Industry Standard

Glass decanters for regular or decaf coffee.

- Provides 10-12 cup capacities.
- Thumb rest on handle ensures greater control and easy pouring.
- Contoured bottle design allows for comfortable fit on warmer plates.




Coffee Decanters

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
98005	3-pack glass decanters with black handle	7" x 6" each
98000	24-pack glass decanters with black handle	7" x 6" each
98006	3-pack glass decanters with orange handle	7" x 6" each
98001	24-pack glass decanters with orange handle	7" x 6" each

Optional Coffee Rack



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 DR-2SU (ADR-2SU)	Black, powder-coated decanter rack, holds 2 decanters, step-up	7.5" x 7.75" x 12.25"



ACCESSORIES

GRINDMASTER




Coffee Airpots

Glass-Lined Push-Top Dispense






MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 AP-3 (AAP-3)	Single (1) 3.0 L airpot	14.5" x 7.25" x 7.25"
 70768-C	Case of (6) 2.2 L airpots	Case of six, each 14.5" x 7.25" x 7.25"

ENAL- Models include colored flavor tags to indicate contents

	Brown for REGULAR Coffee		Orange for DECAF		Green for HOT WATER
---	--------------------------	---	------------------	---	---------------------




Flavor Tags Glass-Lined Lever-Top Dispense



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 ENALG22S (2502-000)	Single (1) 2.2 L airpot	15.5" x 6.25" x 8.5"
ENALG22S (7000-10000)	Case of (6) 2.2 L airpots	case of six, each 15.5" x 6.25" x 8.5"
 ENALG25S (2502-002)	Single (1) 2.5 L airpot	14" x 5.5" x 5.5"
ENALG25S (7000-10002)	Case of (6) 2.5 L airpots	case of six, each 14" x 5.5" x 5.5"
 ENALG30S (2502-004)	Single (1) 3.0 L airpot	16.5" x 7" x 7"
ENALG30S (7000-20001)	Case of (6) 3.0 L airpots	case of six, each 16.5" x 7" x 7"

Flavor Tags Stainless Steel-Lined Lever-Top Dispense



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 ENALS22S (2502-001)	Single (1) 2.2 L airpot	15.5" x 6" x 6"
ENALS22S (7000-10001)	Case of (6) 2.2 L airpots	case of six, each 15.5" x 6" x 6"
 ENALS25S (2502-003)	Single (1) 2.5 L airpot	14" x 5.5" x 5.5"
ENALS25S (7000-20000)	Case of (6) 2.5 L airpots	case of six, each 14" x 5.5" x 5.5"
 ENALS30S (2502-005)	Single (1) 3.0 L airpot	16.5" x 7" x 7"
ENALS30S (7000-20002)	Case of (6) 3.0 L airpots	case of six, each 16.5" x 7" x 7"

ACCESSORIES

GRINDMASTER

Coffee Warmers

Coffee Ready and Waiting

Expand your brewing center by combining multiple warmers with your brewers.

- Attractive appearance complements any decor.
- Space saving designs.
- Stainless steel construction with black warmer plates.


Glass-Lined Push-Top Dispense



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	BW-2 (ABW-2)	(2) side-by-side warmers	3.5" x 14" x 7.25"
	BW-2SU (ABW-2SU)	(2) warmers, step-up	5.5" x 7" x 14"

Coffee Brew Basket & Filters

Brew Baskets

	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	71952	Plastic brew basket	3.63" x 7.63" x 9"
	71619	Stainless steel brew basket	3.63" x 7.63" x 9"
	A71431	Stainless steel gourmet brew basket	5" x 7.63" x 9"












Brew Baskets

MODEL	DESCRIPTION
A06513-04	12-cup, 4.5" bottom, 2.6" sidewall filter paper 1,000 per box

ACCESSORIES

GRINDMASTER

Coffee Airpots Racks & Systems

	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	70583	Holds 2 cream or sugar canisters or multiple packets in rear compartment	7" x 7" x 11"
	70620	2 airpot rack only (2 inline)	16" x 7.25" x 21"
	70759	2 airpot rack with 2 lever-top airpots (2 inline, black)	23" x 7.25" x 21.5"
	70577	2 airpot rack only (2 airpots side-by-side)	9" x 14" x 12"
	70571	3 airpot rack only (3 airpots side-by-side)	9" x 21.5" x 11.25"
	70576	Rack only: Riser for 2 airpots	11.5" x 10.75" x 10.25"
	70575	Rack only: Riser for 3 airpots	10" x 19" x 10.75"
	70758	4 airpot rack with 4 lever-top pots. Racks are 2 airpots wide with a riser for 2 airpots	15.5" x 27" x 12"
	70757	6 airpot rack with 6 lever-top pots. Racks are 3 airpots wide with a riser for 3 airpots	15.5" x 41" x 11.75"
	70659	2 airpot rack with 2 lever-top pots (2 side-by-side)	16.25" x 14.5" x 12"
	70651	3 airpot rack with 3 lever-top pots (3 side-by-side)	16" x 21.5" x 11.25"

COFFEE URNS

GRINDMASTER

PrecisionBrew® Barista Series Urns

Signature Cup


PrecisionBrew® technology gives user complete control over the brew cycle, contact time, and brew temperature, and holds the water temperature to + /- 1 °F.

- Three independent batch-volume sizes per liner.
- Each batch can be programmed with pulse brewing feature.
- Dual wall, air-insulated, electropolished liners maintain steady temperature. Brews at 200°F, and holds coffee at 185°F.
- Programmable, energy-saving 'sleep mode' feature - every day can be individually programmed to be warmed up and ready to brew when you open, and turn off when you close.
- Low Temp - No Brew function.
- Coffee levels are displayed as an easy-to-read LED light graph.
- Automatic Air Agitation ensures that every cup has the same profile.



Single Barista Series Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 PB-8113E (APB8113EP)	Pump style (1) liner, 3 gallons 120/208V / 8.0 kW / 38A / 1 Ph 120/240V / 10.5 kW / 28A / 1 Ph Line cord not included.	28" x 19" x 20"

Twin Barista Series Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
PB-8103E (APB8103E)	Heat exchange style standard (2) liners, 3 gallons each 120/208V / 11.5 kW / 54A / 1 Ph 120/240V / 15.0 kW / 63A / 1 Ph Line cord not included.	28" x 31.5" x 20"

Electrical: Specify 3 phase if needed. See available options on page 32.

Note: Accessories sold separately. See pages 33 - 34.

Note: Order ABB3WP filters. See page 35.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Space Saver Urns

Of Course We Have Coffee!


Space Saver Coffee Urns are the hassle-free, automatic, and efficient way to produce premium quality coffee. With so many automatic features, and its constant brew temperature, preparing fresh coffee for a crowd has never been simpler.

- Fully automatic, push-button operation.
- Brew temperature remains constant with less than 5° F variation.
- Dual wall fiberglass insulation saves energy and minimizes heat loss.
- Automatic coffee agitation and automatic refill/reheat of water.
- Low water cutoff system protects heating elements from burn out.



Single Space Saver Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 8116E (A8116E)	Heat exchange style (1) liner, 6 gallons 120/208V / 11.5 kW / 54A / 1 Ph 120/240V / 15.0 kW / 63A / 1 Ph Line cord not included.	35" x 22" x 17.75"

Twin Space Saver Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
8106E (A8106E)	Heat exchange style (2) liners, 6 gallons each 120/208V / 15.0 kW / 72A / 1 Ph Line cord not included.	33.5" x 35" x 17.75"

Electrical: Specify 3 phase if needed. See available options on page 32.

Note: Accessories sold separately. See pages 33 - 43.

Note: Order filter ABB3WP for 3 gallon urns, ABB6WP for 6 gallon urns. See page 35.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Midline Pump Urns

One-Button Brewing


Effortless, automatic, and premium coffee are all possible! These solid performers are simple to use, dependable, and produce an exceptional cup of coffee.

- Pump type brewing system - water is heated in large water storage compartment. When brew button is activated, hot water is pumped over the coffee grounds through specially-designed solid cone spray nozzle, providing the most uniform extraction possible from the coffee bed.
- All A.I.S.I. type 304 18-8 stainless steel, single-wall construction.
- Automatic coffee agitation and automatic refill/reheat of water.
- Low water cutoff system protects heating elements from burn out.
- Half batch / full batch capability.
- Closed chamber brewing prevents escape of coffee vapors and loss of aroma and flavor.




Single Midline Pump Urns



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
7713E (A7713E)		(1) liner, 3 gallons 120/208V / 5.5 kW / 25A / 1 Ph 120/240V / 7.0 kW / 29A / 1 Ph Line cord not included.	27.25" x 23.5" x 15.25"
	7716E (A7716E)	(1) liner, 6 gallons 120/208V / 8.5 kW / 41A / 1 Ph 120/240V / 11.5 kW / 48A / 1 Ph Line cord not included.	33.25" x 26.5" x 16.75"

Twin Midline Pump Urns



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	7773E (A7773E)	(2) liners, 3 gallons each 120/208V / 5.5 kW / 25A / 1 Ph 120/240V / 7.0 kW / 29A / 1 Ph Line cord not included.	27.25" x 36" x 15.25"
7776E (A7776E)		(2) liners, 6 gallons each 120/208V / 8.5 kW / 41A / 1 Ph 120/240V / 11.5 kW / 48A / 1 Ph Line cord not included.	33.25" x 39.5" x 16.75"

Electrical: Specify 3 phase if needed. See available options on page 21.

Note: Accessories sold separately. See pages 33-34.

Note: Order filter ABB3WP for 3 gallon urns, ABB6WP for 6 gallon urns. See page 35.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Midline Heat Exchange Urns

Reliable, Durable, Delicious


For energy-efficient brewing that will surpass the expectations of any coffee shop, try this unique fresh water brewing system. Saves energy while brewing premium quality coffee.

- Fresh water brewing - water is brought into the urn immediately before the brew, preventing any staling. The water passes through a heat exchanger coil, and is instantly heated to optimal brew temperature. Saves energy, and preserves taste!
- All A.I.S.I. type 304 18-8 stainless steel, single-wall construction.
- Automatic coffee agitation and automatic refill/reheat of water.
- Low water cutoff system protects heating elements from burn out.
- Velvet smooth spray arm - Teflon® coating on spray arm piston prevents liming and ensures smooth operation.
- Half batch / full batch capability.




Single Midline Heat Exchange Urns



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
7413E (A7413E)		(1) liner, 3 gallons 120/208V / 5.5 kW / 25A / 1 Ph 120/240V / 7.0 kW / 29A / 1 Ph Line cord not included.	27.25" x 23.5" x 15.25"
	7416E (A7416E)	(1) liner, 6 gallons 120/208V / 8.5 kW / 41A / 1 Ph 120/240V / 11.5 kW / 48A / 1 Ph Line cord not included.	33.25" x 26.5" x 16.75"

Twin Midline Heat Exchange Urns



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
7443E (A7443E)		(2) liners, 3 gallons each 120/208V / 5.5 kW / 25A / 1 Ph 120/240V / 7.0 kW / 29A / 1 Ph Line cord not included.	27.25" x 36" x 15.25"
	7446E (A7446E)	(2) liners, 6 gallons each 120/208V / 8.5 kW / 41A / 1 Ph 120/240V / 11.5 kW / 48A / 1 Ph Line cord not included.	33.25" x 39.5" x 16.75"

Electrical: Specify 3 phase if needed. See available options on page 32.

Note: Accessories sold separately. See pages 33 - 34.

Note: Order filter ABB3WP filters for 3 gallon urns, ABB6WP for 6 gallon urns. See page 35.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Shipboard Models Midline Heat Exchange Urns

Ship Shape Service

Created specifically for shipboard use, these state-of-the-art coffee urns provide every convenience when you are sailing the seas.

- Anti-splash baffle in water compartment.
- Larger capacity coffee liner prevents spills.
- Reusable, washable muslin bags (25 ea) instead of paper filters.
- Drilled and tapped bullet feet, bolts included.
- Heat exchange type brewing saves energy.
- No air agitation for coffee (auto or manual).
- Low water cutoff system protects heating elements from burn out.
- Auto refill.
- Half/full batch capability.




Single Midline Heat Exchange Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
7413E (A7413EX SHP)	3 gallon urn with (1) liner, 4 gallons 440V / 10 kW / 13A / 3 Ph / 3W + G Step down transformer for 120V controls built in. Line cord not included.	24.25" x 23.5" x 18"

Twin Midline Heat Exchange Urns



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 7443E (A7443EX SHP)	3 gallon urn with (2) liners, 4 gallons each 440V / 10 kW / 13A / 3 Ph / 3W + G Step down transformer for 120V controls built in. Line cord not included.	24.25" x 36" x 15.25"

Note: No bypass valve.

Note: Order brew basket ABB3 for 3 gallon urns, and ABB6 for 6 gallon urns. See page 34.

* Unit does not ship with a cord or plug. Please contact Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Single 3 Gallon Models

Keeps Up With Customer Demand

Perfect for high volume coffee environments, the compact construction is a valuable asset to any operation with limited countertop space.

- Solid-state dual water level control.
- Stainless steel, single-wall construction.
- Silicone fittings prevent corrosion, pitting, and leakage.
- Thermostat on side box for easy access and service.
- Pump-style brewing.
- 3 gallon tank.
- Adjustable by-pass.




Automatic Agitator Urn



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
FE75N (101805)	Automatic agitator, solid-state timer 120/208V / 5.3 kW / 26A / 1 Ph 120/240V / 7 kW / 30A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	28.5" x 21.5" x 14"
FE75N 3 Phase (101806)	Automatic agitator, solid-state timer 120/208V / 4.5 kW / 13A / 3 Ph 120/240V / 6 kW / 15A / 3 Ph Line cord not included. Plumbing: 0.25" water line required.	28.5" x 21.5" x 14"

Manual Agitator Urn



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 CL75N (118802)	Push button agitator, electro-mechanical timer 120/208V / 5.3 kW / 26A / 1 Ph 120/240V / 7 kW / 30A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	28.5" x 21.5" x 14"

Note: Accessories sold separately. See pages 33 - 34.

Note: Order filter ABB6WP. See page 35.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Twin 3 Gallon Models



Simple Operation

With a six-gallon capacity, you can quickly brew all of the piping hot coffee you need to keep your customers' coffee mugs filled during high-volume hours.

- Solid-state dual water level control.
- Stainless steel, single-wall construction.
- Silicone fittings prevent corrosion, pitting, and leakage.
- Modern look and user-friendly operation.
- Thermostat sensor on side box for easy access and service.
- Pump-style brewing.
- Two 3 gallon tanks (6 gallon total capacity).
- Adjustable by-pass.



Automatic Agitator Urn

MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
FE100N (102417)		Automatic agitator, solid-state timer 120/208V / 6 kW / 29 A / 1 Ph 120/240V / 8 kW / 34A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	29.1" x 33.4" x 14" 
	FE100N 3 Phase (102418)	Automatic agitator, solid-state timer 120/208V / 6 kW / 17 A / 3 Ph 120/240V / 8 kW / 20A / 3 Ph Line cord not included. Plumbing: 0.25" water line required.	29.1" x 33.4" x 14"

Manual Agitator Urn



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
CL100N (117402)		Push button agitator, electro-mechanical timer 120/208V / 5.3 kW / 26 A / 1 Ph 120/240V / 7 kW / 30A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	29.1" x 33.4" x 14"

Note: Accessories sold separately. See pages 33 - 34.

* Unit does not ship with cord or plug. Please contact a Local Qualified Service Agency for installation.

COFFEE URNS

GRINDMASTER

Twin 6 Gallon Models

Consider the Crowds Tamed


Make high volume coffee operation simple and seamless, and deliver delicious drinks with the 12 gallon capacity urn.

- Two brew batch sizes at the push of a button for high and low volume periods.
- Adjustable by-pass system.
- Automatic refill ensures fresh hot water
- Automatic agitation blends coffee at end of each brew cycle.
- Cycle stop switch provides ability to stop brew cycle midstream.
- Thermometer indicates optimum brewing temperature.
- Durable stainless steel construction.
- Pump-style brewing.
- Two 6 gallon tanks (12 gallon total capacity).



Automatic Agitator Urn



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	FE200 (104400)	120/208V / 7.5 kW / 37A / 1 Ph 120/240V / 10 kW / 42A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	33" x 37.5" x 16"
	FE200 3 Phase (104415)	120/208V / 7.5 kW / 21A / 3 Ph 120/240V / 10 kW / 25A / 3 Ph Line cord not included. Plumbing: 0.25" water line required.	33" x 37.5" x 16"

Note: Accessories available separately. See pages 33 - 34.
Note: Order ABB6WP filters. See page 35.

ELECTRICAL OPTIONS

GRINDMASTER

For Coffee Urns

Electrical Options: 120/208V

Model	AOPT 21AU	AOPT 21AU6	AOPT 21AU610
Description	120/208V / 3 Ph	120/208V / 3 Ph	120/208V / 3 Ph
For Use With	Midline 3 gallon urns	Midline 6 gallon heat exchange urns	Midline 6 gallon pump urns

Electrical Options: 208/240V

Model	AOPT 21BU3	AOPT 21BU610
Description	208/240V / 0.003 kW / 3 Ph	208/240V / 3 Ph / 0.003 kW. For use with midline 6/10 gallon urns

Electrical Options: 480V

Model	AOPT 21CU3	AOPT 21CU610	AOPT 21CUTL3	AOPT 21CUTL610
Description	480V / 0.003 kW / 3 Ph	480V / 0.003 kW / 3 Ph	480V / 0.003 kW / 3 Ph	480V / 0.003 kW / 3 Ph
For Use With	Midline 3 gallon urns	Midline 6/10 gallon urns	Space saver 3 gallon urns	Space saver 6/10 gallon urns

Electrical Options: Transformers

Model	AOPT 2200	AOPT 2200P
Description	Transformer for heat exchange urns: 2 wire	Transformer for pump urns: 2 wire

OPTIONS

GRINDMASTER

For Coffee Urns

Double Service Package Options

Model	AOPT DS101 to DS108	AOPT DS201 to DS206	AOPT TS103 to TS104	AOPT TS204 to TS206
Description	Service, double faucets, gauge on operator side only	Service, double faucets, gauge on both sides	Service, double faucets, gauge on operator sides	Service, double faucets, gauge on both sides
For Use With	Midline/spacesaver urns	Midline/spacesaver urns	Triple urns	Triple urns

Low Temp No Brew

Model	AOPT 47U00	AOPT 47U01
Description	Low Temp No Brew	Low Temp No Brew
For Use With	Single and twin urns	Triple urns

Prison Packages

Model	AOPT 10B	AOPT 10B3
Description	Prison package	Prison package
For Use With	Twin midline urns: 6 gal.	Twin midline urns: 3 gal.

Prison Packages

Model	AOPT 10SB610	AOPT 10SSS
Description	Prison package	Prison package
For Use With	Single midline urns: 6 gal.	Single space saver urns: 6 gal.

ACCESSORIES

GRINDMASTER

For Coffee Urns

Accessories

Model	AOPT 45	AOPT 4400U	AOPT 5800	AOPT 5700
Description	Bullet feet, drilled and tapped	Flanged feet	Higher legs	Gravity jug fill

Accessories

Model	AOPT 7100	AOPT 93L3 to 93WB
Description	Vacuum Breaker	Control Cover with Lock for all space saver urns

COFFEE BREW BASKETS

GRINDMASTER

For Coffee Urns

3 Gallon Urns

Model	ABB3	ABB3-1.5	A#153
Description	Brew basket	Brew basket, half batch	Brew basket, permanent stainless steel screen

6 Gallon Urns

Model	ABB6	ABB6-3	A#156
Description	Brew basket	Brew basket, half batch	Brew basket, permanent stainless steel screen

COFFEE FILTERS

GRINDMASTER

For Coffee Urns

3 Gallon Urns

Model	ABB1.5WP	ABB3WP
Description	13" diameter, 5" bottom 500 per box	18" diameter, 6" bottom 500 per box
For Use With Brew Basket	Half-batch brew basket ABB3-1.5	ABB3
Ship Dimensions (H x W x D)	8.9" x 12.2" x 9"	15.75" x 11.75" x 11.75"

6 Gallon Urns

Model	ABB3WP	ABB6WP	820 (F820U)
Description	18" diameter, 6" bottom 500 per box	500 per box	20" diameter, 8" bottom 500 per box
For Use With Brew Basket	Half-batch brew basket ABB6-3	ABB6	ABB6
Ship Dimensions (H x W x D)	15.75" x 11.75" x 11.75"	16" x 20.5" x 13.75"	16" x 20.75" x 13.75

ICED TEA DISPENSERS

GRINDMASTER

Front of the House Stainless Steel Tea Dispensers

Streamlined and Elegant, With No Liner Required!

The attractive finish is polished and professional. It's large 3 gallon capacity is perfect for self-service beverage areas. Simple to use, easy-to-clean, hard-wearing. We are still trying to find something we don't like about these dispensers.

No Liner Needed

Passivated interior and exterior protects the flavor of the beverage, and does not require the use of a liner. This makes these dispensers easier to clean and sanitize than plastic urns on the market, with substantial cost savings and environmental benefit.

Rugged Construction

Stainless steel construction and faucet connection withstands heavy use, is rust resistant, and easy to clean. Laser welds are heavy duty, stand up to repeated use, and resist leakage.

Easy Brewing and Dispensing

Fits under most commercial brewers - just remove the lid and brew directly into the dispenser. With four dispensers to choose from, you can select the perfect one for your usage.

Cleaning Made Simple

All parts and components are removable, allowing it to be easily and thoroughly cleaned.

Effortless Transportation

Stainless steel handles make it easy to lift and carry.

9 ½" Cup Clearance

Easily fill large to-go cups or tall iced tea glasses.

Slim Design, Considerable Capacity

Its large 3 gallon size guarantees that your drinks will be in good supply, and its compact design allows it to easily fit where you need it, and not waste much-needed counter space.



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	GTD3-DNT (6700-20001)	Tomlinson® down-facing valve	22" x 6" x 13.5"
	GTD3-FOT (6700-30000)	Tomlinson® front valve	22" x 6" x 13.5"
	GTD3-TP (6700-30001)	Tomlinson® front valve with pinch tube	22" x 6" x 13.5"
	GTD3-C (6700-40000)	Crathco® valve. Designed to allow for one-hand operation	22" x 6" x 13.5"

ICED TEA DISPENSERS

GRINDMASTER


S Series Stainless Steel Tea Dispensers

Cool and Easy

The S Series Stainless Steel Tea Dispensers are perfect anywhere you or your customers need easy access to delicious iced tea. Featuring Tomlinson no-drip faucets to protect from potential drips and spills, the series offers dispensers from 2 - 10 gallons in size, with or without handles.

They provide an impressive 7" - 9" high faucet clearance, allowing ample room for serving your delicious fresh-brewed iced tea into tall glasses, to-go cups, and beverage pitchers. When finished serving, its cylindrical design makes cleanup quick and easy.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	S2 (442000L)	2 gallon capacity 7" faucet clearance	15" x 9.25"
	S3 (443000L)	3 gallon capacity 7" faucet clearance	19.5" x 9.5"
	S3C (069430L)	3 gallon capacity with handles 7" faucet clearance	19.5" x 9.5"
	S5 (445000L)	5 gallon capacity 7" faucet clearance	26" x 10"
	S5C (445010L)	5 gallon capacity with handles 7" faucet clearance	26" x 10"
	S10 (446500L)	10 gallon capacity 9" faucet clearance	29" x 12.5"
	S10C (446511L)	10 gallon capacity with handles 9" faucet clearance	29" x 12.5"
	B1/3 Dispenser & Base (069370L)	3 gallon capacity	22" x 12.5" x 12.5"
	B1/3T Dispenser (069380L)	3 gallon capacity	14" x 10" x 14"
	SU3P Dispenser & Base (069480L)	3.5 gallon capacity	18.75" x 9.25" x 9.25"

HOT TEA URNS

GRINDMASTER

Chinese Hot Tea Urns

Hot Tea Made Simple

The Chinese Hot Tea Urn is a twin style unit with 3 gallons in each urn, for a total capacity of 6 gallons. A seamless urn liner and silicone fittings prevent corrosion, pitting, and leaking, and enable the urn to withstand constant use. The urn automatically fills with water thanks to the solid state dual water level controls.

Construction of stainless steel makes it durable, easy to clean, and reliable. Tea can be brewed in half or full batches to ensure minimal end-of-day waste.

- Silicone fittings prevent corrosion, pitting, and leakage.
- Type 304L stainless steel single-wall construction.
- Solid-state dual water level control.
- Thermostat sensor at side box for easy access and service.
- Seamless urn liners standard.
- Easy changing of the water pump or thermostat- no need to empty urn completely.
- Provides (2) brew cycle choices, full batch and half batch. Full batch standard, half batch optional.
- Electro-mechanical timer, adjustable by-pass, push-button agitator



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
CH100N (119905)	(2) liners, 3 gallons each 120/240V / 8 kW / 34A / 1 Ph 120/208V / 6 kW / 29A / 1 Ph Line cord not included. Plumbing: 0.25" water line required.	28.5" x 33.5" x 14"

* Unit does not ship with cord or plug. Please contact Local Qualified Service Agency for installation.

Brew Baskets and Filter Paper

MODEL	DESCRIPTION
V002A	Stainless steel brew basket
ABB3WP	18" diameter, 6" bottom filter paper 500 per box

HOT WATER HEATERS

GRINDMASTER

ME Series Water Heaters

The Perfect Addition

Investing in a hot water heater from the ME Series is a wise, economical addition to your business. They provide you with a convenient, affordable way of keeping piping hot water flowing for the preparation of your hot chocolate, tea, Americanos, and more! The automatic refill system ensures you're never caught unprepared, their solid state liquid level control system provides added peace of mind.

Models are available with either a 10 or 15 gallon capacity, so you will have a constant source of hot water, and the no-drip faucet guarantees that the water stays put until you need it.

- Electronic solid state water level control for automatic refill.
- Precision multi-setting thermostat with hold setting.
- Dial thermometer for exact temperature reading.
- Type 304L stainless steel construction for long-lasting service.
- Accurate water level gauge.
- Reliable no-drip faucet with sight glass and water shut off.



10 Gallon Models



15 Gallon Models

10 Gallon Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
ME10EN (121505)	120V / 1.8 kW / 15A / 1 Ph; NEMA 5-15P line cord included Plumbing: 0.25" water line required.	26" x 18" x 20"
ME10EN (121511)	208V / 5.3 kW / 26A / 1 Ph 240V / 7.0 kW / 30A / 1 Ph Line cord not included Plumbing: 0.25" water line required.	26" x 18" x 20"
ME10EN (121521)	208V / 7.9 kW / 22A / 3 Ph 240V / 10.5 kW / 25A / 3 Ph Line cord not included Plumbing: 0.25" water line required.	26" x 18" x 20"

15 Gallon Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
ME15EN (121574)	120V / 1.8 kW / 15A / 1 Ph; NEMA 5-15P line cord included Plumbing: 0.25" water line required.	31" x 18" x 20"
ME15EN (121561)	208V / 5.3 kW / 26A / 1 Ph 240V / 7.0 kW / 30A / 1 Ph Line cord not included Plumbing: 0.25" water line required.	31" x 18" x 20"
ME15EN (121571)	208V / 7.9 kW / 22A / 3 Ph 240V / 10.5 kW / 25A / 3 Ph Line cord not included Plumbing: 0.25" water line required.	31" x 18" x 20"

HOT WATER HEATERS



Heavy Duty Hot Water Heaters

Auto Refill and Reheat

- Water temperature is maintained between 190°F and 200°F.
- Water compartment automatically refills and reheats as necessary.
- Dial thermometer with color-marked temperature zone.
- Type 304L stainless steel construction.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
830E (A830E)	30 gallon capacity 120/208V / 11.5 kW / 54A / 1 Ph 120/240V / 15.0 kW / 72A / 1 Ph Line cord not included. Plumbing: 3/8" FPT water inlet	27" x 26" x 16.75"
850E (A850E)	50 gallon capacity 120/208V / 11.5 kW / 54A / 1 Ph 120/240V / 15.0 kW / 72A / 1 Ph Line cord not included. Plumbing: 3/8" FPT water inlet	32" x 26" x 16.75"

Optional Prison Package for 830E and 850E

MODEL	DESCRIPTION
AOPT 10WB	Prison package

HOT WATER DISPENSERS

GRINDMASTER

WH Series Hot Water Dispensers

Constant Temperature

Don't let the compact footprint of the WH Series of hot water dispensers fool you. Although they take up minimal space in your kitchen, they provide an inexhaustible supply of hot water that is held at a constant temperature up to 200°F. 1.3-, 2.6, and 5.3-gallon models are available with your choice of tap operated dispense or push button dispense.

- 1.3-, 2.6-, and 5.3-gallon options (5.3-gallon tap operated only)
- Easy to descale
- Made from 95% recyclable materials
- Up to 7.3 gallons output per hour
- Up to 156 cups (6 oz.) per hour
- Removable drip tray.



Tap Operated Hot Water Dispensers



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	WHT5 (2403-000)	1.3 gallon, 120V/1PH/60HZ, 1.45 Kw - NEMA 5-15P	18.3" x 8.2" x 20.2"
	WHT5 (2403-001)	1.3 gallon, 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P	18.3" x 8.2" x 20.2"
	WHT10 (2403-002)	2.6 gallon, 120V/1PH/60HZ, 1.45 Kw - NEMA 5-15P	23.2" x 8.2" x 20.2"
	WHT10 (2403-003)	2.6 gallon, 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P	23.2" x 8.2" x 20.2"
	WHT20 (2403-004)	5.3 gallon, 240V/1PH/60HZ, 1.45 Kw - NEMA 5-15P	27.2" x 9.4" x 22.3"
	WHT20 (2403-005)	5.3 gallon - 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P	27.2" x 9.4" x 22.3"

Accessories for WHT Models

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
410-00842	Hands-Free Tap Adapter Specially-designed curved adapter reduces the risk of contact between the cup lip and the tap	6.1" x 2.7" x 1.4"

HOT WATER DISPENSERS




GRINDMASTER

WH Series Hot Water Dispensers



Push Button Operated Hot Water Dispensers



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 WHP5 (2403-006)	1.3 gallon - 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P	18.3" x 8.2" x 18.2"
 WHP10 (2403-007)	2.6 gallon - 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P	23.2" x 8.2" x 18.2"
 WHP10HI (2403-0008)	2.6 gallon - 240V/1PH/60HZ, 2.9 Kw - NEMA 6-15P Includes LCD screen for precise temperature control	26.5" x 8.2" x 18.2"

Accessories for Push Button Operated Hot Water Dispensers


MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
410-00843	WH Button Adapter Specially designed push-button adapter to eliminate button interaction.	6.25" x 2.75" x 1"

Portable Coffee & Hot Water Dispensers

Hot Drinks To Go!

- Ideal for hot coffee or hot water.
- Portable, easily moved to any convenient location.
- Precision thermostat for accurate temperature control.
- Sight glass indicates water level.
- Type 304L stainless steel construction.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 CS113 (431500L)	3 gallon capacity 120V / 1.65 kW / 13.8A / 1 Ph NEMA 5-15P line cord included.	21" H x 11" Diameter
CS115 (432500L)	5 gallon capacity 120V / 1.65 kW / 13.8A / 1 Ph NEMA 5-15P line cord included.	26.5" H x 11" Diameter

POWDERED BEVERAGE DISPENSERS

GRINDMASTER

PIC Powdered Beverage Dispensers

Simple Satisfaction



PIC Hot Powdered Beverage Dispensers are perfect for dispensing a variety of products, including great tasting, high quality cappuccinos, gourmet hot cocoas, chai teas, and hot apple cider.

- Large, operator friendly, Clear-View™ hoppers.
- Direct drive hoppers – self-aligning for durability and easy install.
- Patented safety rib on dispense nozzle and cup guide on the drain tray.
- Generous cup clearance for popular large sizes.
- Attractive front-lit graphics encourage impulse buys.




Three Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 PIC3 (61005D)	3 hoppers, 5 lbs. capacity 120V / 1.4 kW / 14A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	26.5" x 12" x 22"
 PIC33A (61052D)	3 hoppers, 5 lbs. capacity, 3 volume options per head 120V / 1.4 kW / 14A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	26.5" x 12" x 22"
Planned Maintenance Kit	Six Month Schedule	250-00112

Five Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 PIC5 (62933)	5 hoppers, 5 lbs. capacity 120V / 1.4 kW / 14A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	36" x 20" x 25.5"
Planned Maintenance Kit	Six Month Schedule	250-00113

Optional External Water Pump Kit



MODEL	DESCRIPTION
63174	External Water Pump Kit: allows unit to operate in remote location from bottled water

POWDERED BEVERAGE DISPENSERS

GRINDMASTER

GB Powdered Beverage Dispensers

Delicious Flavor, Optimal Variety


The GB Series of Powdered Beverage Dispensers guarantees that you have the right variety of high-quality beverages for any customer's taste.

- Vacuum Steam Removal System ensures the powdered mix remains dry, to eliminate clogging, caking, and bridging.
- Moisture and powder collection tray prevents excess moisture and product powder from reaching the vacuum motor.
- Self cleaning rinse system is touch-button easy and rinses the entire whipper chamber with hot water at the end of each cycle.





Single Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 GB1HC-CP (08003QL)	Moderate volume, (1) hopper, 8 lbs. capacity Non-lit, right side hinge door. 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	26" x 7.75" x 19"
Planned Maintenance Kit	6 Six Month Schedule	250-00105


Two Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 GB2HC-C (08003TL)	Moderate volume, smallest footprint available (2) hoppers, 4 lbs. capacity each. Non-lit, right side hinge door. 120V / 1.8 kW / 15A / 1 Ph. NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	24" x 7.75" x 19"
 2K-GB-LD (080022L)	Low to medium volume, (2) hoppers, 4 lbs. capacity each 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	34.25" x 8.5" x 23"
Planned Maintenance Kit	6 Six Month Schedule	250-00106

Four Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 4K-GB-LD (080041L)	Low to medium volume, (4) hoppers, 4 lbs. capacity each 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	31.5" x 15.6" x 20"
Planned Maintenance Kit	6 Six Month Schedule	250-00108

POWDERED BEVERAGE DISPENSERS


GRINDMASTER

GB Powdered Beverage Dispensers




Six Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 GB6M10-LD-U (080152L)	High volume, (1) hopper, 10 lbs. capacity, (5) hoppers, 5 lbs. capacity each. 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included. Plumbing: 0.25" water line required.	34.25" x 21.75" x 22"
Planned Maintenance Kit	6 Six Month Schedule	250-00110

Eight Flavor Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 GB8MP-10-LD-U* (080167L)	High volume, (1) hopper, 10 lbs. capacity, (7) hoppers, 5 lbs. capacity each. (2) 120V / 1.8 kW / 15A / 1 Ph (2) NEMA 5-15P line cords included. Plumbing: 0.25" water line required.	35" x 27.25" x 24"
Planned Maintenance Kit	6 Six Month Schedule	250-00111

HEATED DISPENSERS



Lola Series Hot Dispensers

Thick, Rich, and Hot

Perfect for heating and dispensing thick chocolate, hot cider, and other hot beverages. Use as a heated dispenser for mixtures with no particulates that need to be served warm and require agitation to prevent separation.

- Adjustable thermostat up to 194° F.
- Vertical tap for free flow. Easy to clean and disassemble.
- Transparent bowl encourages impulse use.
- Attractive design allows for use in any location: as a counter-top dispenser, in the buffet line, or in the kitchen.
- Easily removable bowl even when full for refrigerated storage.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
Lola 6 (2505-001)	(1) 1.32 gallon capacity, black finish	18.3" x 10.6" x 12.5"

SUPER-AUTOMATIC ESPRESSO MACHINES

UNIC

Tango Milk Series

Super-Automatic One-Step with real Milk

Automatically Delicious

Exceptional quality in a variety of drinks with little operator skill. All models can be public-facing in some areas. Push a button and the machine will grind the beans, pull the extraction, froth and steam its refrigerated milk, and add it into the drink.





Touchscreen Interface Offers Programmable Control of:

- 48 drink recipes per grouphead
- 2 separate coffee grinds
- 2 pre-infusion methods
- Boiler temperature
- Tamping
- Coffee dose and water dose

Easy use makes it a great choice for locations where espresso is not the focus, or with seasonal employees. Perfect in cafés, cafeterias, offices, refreshment areas for business, education, and hospitals.

- Integrated SteamAir wand with auto milk foamer and programmable temperature control.
- Quick clean cycles every 90 drinks; complete group auto clean cycle every 24 hours.
- ACE L/C, ST Solo L/C and ST Duo L/C offer temperature regulation for the steam and the group.
- Includes installation by a Unic certified service provider.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 ACE L/C Milk (1011-004)	Public facing and attended service, (1) group with double spouts, (2) coffee bean hoppers: 3.75 lbs. and 2.6 lbs., (2) precision grinders with 64 mm Mahlkonig burrs, one-gallon pump refrigerator	Without refrigerator: 33" X 18" X 24" With refrigerator: 33" X 27" X 24" Height includes 3" stainless steel legs.
 ST Solo Milk (1011-005)	Public facing and attended service, (1) group with double spouts, (2) coffee bean hoppers: 3.75 lbs. and 2.6 lbs., (2) precision grinders with 80 mm Mahlkonig burrs, Shown with 2-Gallon Tango L/C Fridge	Without refrigerator: 33" x 18" x 24" With refrigerator: 33" x 28" x 24" Height includes 3" stainless steel legs.
 ST Duo Milk (1011-006)	Public facing and attended service, (2) groups with double spouts, (2) 3.75 lbs. coffee bean hoppers, (2) precision grinders with 80 mm Mahlkonig burrs. Shown with 2-Gallon Tango L/C Fridge. Can work with 2 Fridges for 2 different milk types	Without refrigerator: 33" X 24" X 24" With refrigerator: 33" X 34" X 24" Height includes 3" stainless steel legs.
 Two-gallon Tango ST L/C Refrigerator (2901-000)	Designed to be placed next to an espresso machine, Completely insulated and refrigerating a US 1-gallon container of milk. Built-in side hose hole. External Digital Thermostat Control	16" X 9" X 24"

SUPER-AUTOMATIC ESPRESSO MACHINES



Tango Series
Super-Automatic Two-Step

Loved by All

A beginning barista will appreciate the easy use, and a skilled barista will love the control. The beans are ground and espresso pulled by the machine, but the user mixes the steamed or frothed milk and other flavorings for each drink.

Programmable Automatic SteamAir wand controls the temperature and foam time to create the perfect milk to add to each drink, which gives you more control over amount and type of foam, froth, and milk in the drink, and lets you steam non-coffee drinks like chai tea and hot chocolate.




Touchscreen Interface Offers Programmable Control of:

- 48 drink recipes per grouphead
- 2 separate coffee grinds
- 2 pre-infusion methods
- Boiler temperature
- Tamping
- Coffee dose and water dose

Produces a delicious drink even with an operator who has only basic skills, and offers more skilled baristas greater variety and control. Made-to-order for cafés, hotels, bakeries, coffee shops, cafeterias, restaurants, drive-thrus, or foodservice.

- Programmable hot water dispenser for other hot drinks.
- Quick clean cycles every 90 drinks; complete group auto clean cycle every 24 hours.
- Includes installation by a Unic certified service provider.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	ACE (1011-001)	One group with double spouts, (2) coffee bean hoppers: 3.75 lbs. and 2.6 lbs., (2) precision grinders with 64 mm Mahlkonig burrs	32" X 18" X 24" Height includes 3" stainless steel legs.
	ST Solo (1011-002)	One group with double spouts, (2) coffee bean hoppers: 3.75 lbs. and 2.6 lbs., (2) precision grinders with 80 mm Mahlkonig burrs	32" X 18" X 24" Height includes 3" stainless steel legs.
	ST Duo (1011-003)	Two groups with double spouts, (2) 3.75 lbs. coffee bean hoppers (2) precision grinders with 80 mm Mahlkonig burrs	32" X 24" X 24" Height includes 3" stainless steel legs.

AUTOMATED POD ESPRESSO MACHINES

UNIC

Pony Series

Pod Automated Espresso Machine: Available in Two-Step or One-Step with refrigerator

Pod Perfection

Using 45mm ESE coffee pods to pull espressos, and the automatic SteamAir wand to create just-right milk foam, these machines are ideal where quality and consistency are vital, despite multiple users or employee turnover.

Automatic SteamAir wand is pre-programmed to foam milk, controlling temperature and foam time. User mixes the milk and any other flavorings into the drink. The SteamAir wand gives user more control over amount and type of foam, froth, and milk in the drink, and allows for non-coffee drinks like chai tea and hot chocolate to be created.



Touchscreen Interface Offers Programmable Control of:

- 6 volumetric water settings per grouphead
- Pre-infusion

Excellent for locations such as cafés, restaurants, bakeries, smaller coffee shops, bed & breakfasts, and hotels, and the perfect choice for catering.

- Programmable hot water dispenser for other hot drinks.
- Quick clean cycles every 90 drinks; complete group auto clean cycle every 24 hours.
- Includes installation by a Unic certified service provider.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 Pony 2 (1011-007)	One group with double spouts Small to medium capacity, 100-150 drinks daily. Brews 2 espressos simultaneously. 120V / 1.7 kW / 20A / 1 Ph NEMA 5-20P line cord included.	26" X 14" X 23" Height includes 3" stainless steel legs.
 Pony 4 (1011-008)	Two groups with double spouts Medium capacity, 150-200 drinks daily. Brews 4 espressos simultaneously. 230V / 4.5 kW / 30A / 1 Ph Line cord included with no plug. Suggested plug: L6-30P	26" X 25" X 23" Height includes 3" stainless steel legs.

BEAN-TO-CUP COFFEE BREWER




Tango Series
Tango Ace Bean to Cup Coffee Brewer

Freshly Ground and Brewed Coffee Fast

Make the switch to Bean to Cup for a cup of coffee that is delivered faster and fresher than ever before with less operator contact required and no coffee waste. The Tango Ace Bean to Cup benefits from a double infusion chamber, UNIC's coffee extraction expertise, and robust craftsmanship. Equipped with 2 hoppers with high performance 80 mm grinder burrs, the Tango Ace Bean to Cup consistently and quickly prepares a full bodied and rich tasting filter-style coffee. The user interface is intuitive and perfectly adapted for self-service environments. Ideal for use in healthcare and corporate dining locations.

- Starting with whole coffee beans, this single-cup, on-demand brewer creates delicious drip, French press, and pour-over style coffee drinks.
- 2 bean hoppers – 3.75 lbs. and 2.6 lbs. with low beans warning.
- Hopper stoppers for each hopper – allows for easy removal of hoppers.
- 2 precision grinders with 80 mm Mahlkonig burrs.
- Adaptable for various coffee profiles and exceptional extraction quality obtained through full control of 8 infusion parameters: 2 grinders; temperature; tamping; 2 pre-infusion methods; weight of coffee; volume of water.
- Touch screen displays your customizable taste profiles.
- Large waste bin with overflow safeguard holds up to 120 cycles of used ground.
- Day/night mode.
- Drink counter and cup warmer.
- Quick clean cycles every 90 drinks; complete group auto clean cycle every 24 hours.
- Stainless steel panels and steel framework.
- Full sized rotary vane pump.
- Adjustable and transferable settings via touch screen or USB key.
- Includes installation by a UNIC certified service provider.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	BTC (1011-013)	(2) coffee bean hoppers: 3.75 lbs. (1.7 kg) and 2.6 lbs. (1.2 kg), (2) precision grinders with 80 mm Mahlkonig burrs	32" X 18" X 24"

TRADITIONAL VOLUMETRIC ESPRESSO MACHINES

UNIC

Classic Series



**Espresso equipment designed
for professional use and a sensible budget.**

Elegant lines and reliable technologies appreciated by coffee professionals, the CLASSIC series is made more attractive by its quality/ price ratio. Designed and manufactured by UNIC, the CLASSIC series including the models CLASSIC 1 and CLASSIC 2, is the perfect traditional espresso machine to ensure an excellent quality espresso result, and consistency even during the busiest periods of the day.

Choose a single-group or two-group machine. Each model features heavy duty components and welded construction, a direct mounted boiler group head for thermal stability and reliable extraction, easy access to components for uncomplicated serviceability, and unlimited steam. With its easy operation and serviceability, the CLASSIC series offers technical features ensuring outstanding coffee throughout the day:

- 4 programmable volume keys
- Semi-automatic key for manual control
- Integrated shot timer
- Steam operated through switch with on, off and pulse positions
- Hot water dispenser with flow regulation
- Direct to boiler mounted group head for shot temperature stability
- Overabundant steam supply to eliminate recovery time
- Built-in cup warmer
- Includes installation by a UNIC certified service provider.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	CLASSIC 1 110 (CLN1C000ADEB14)	One group with double spouts, (1) SS steam arm, (1) hot water outlet; Small capacity, 50-100 drinks daily. Brews 2 espressos simultaneously. 110 V – 1700 W – 20 A	23" X 14" X 22"
	CLASSIC 2 (CLN2CC00ADE814)	Two groups with double spouts, (2) SS steam arms, (1) hot water outlet; Medium capacity, 150-200 drinks daily. Brews 4 espressos simultaneously. 230 V – 4600 W – 30 A – Single Phase	23" x 25" x 23"



TRADITIONAL VOLUMETRIC ESPRESSO MACHINES



Mira Series




Extraordinary Flexibility for an Automatic!

Incredibly versatile MIRA series can switch from standard groupheads to pods and capsules for more automation, then quickly switch back again. Allows the barista precise control over the grind, dose, and tamp of every drink, while the machine takes care of the extraction. Or, switch to more automation and ease with pods!

Preset volumes are programmed for a variety of drinks, guaranteeing consistent shots every time even with different baristas. A manual override button lets the operator control the shot size, allowing for custom drinks. Barista can multi-task and steam milk while shot is being pulled, allowing for better productivity.

- 4 programmable volumes plus manual per grouphead.
- Hot water dispenser for additional drinks.
- User monitors and adjusts for correct brew and steam temperature.
- Automated back-flushing cycle for daily cleaning.
- Integrated running shot timer.
- Solid Teflon steam wands for easy cleaning.
- Direct-to-boiler mounted grouphead for shot temperature stability.
- Twin pressure gauge for pump and steam.
- Diagnostics display for easy trouble shooting.
- Includes installation by a Unic certified service provider.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	MIRAHP (1011-014)	Single group with tall double spouts, (1) solid Teflon steam wand. <i>Pair with HC-600 Timer Grinder-Doser</i>	26"X 14"X 23" Height includes 3" stainless steel legs.
	Twin MIRAHP (1011-015)	Two groups with tall double spouts, (2) solid Teflon steam wands, programmable timing for right steam wand. <i>Pair with VGA Automatic Grinder-Doser</i>	26"X 39"X 24" Height includes 3" stainless steel legs.
	Tri MIRA (1011-011)	Three groups with double spouts, (2) solid Teflon steam wands, programmable timing for right steam wand. <i>Pair with VGHDA Automatic Grinder-Doser</i>	23" X 34" X 23" Height includes 3" stainless steel legs.

TRADITIONAL VOLUMETRIC ESPRESSO MACHINES

UNIC



Aura Series

Extraordinary Flexibility for an Automatic!

Two and Three Group Upscale PID controlled single Boiler Espresso Machine with auto clean and electronic boiler adjustments.
This unit is typically operated in mid to high volume cafés.

- Touch control boxes with LED lighting all around, 4 dosing selection, Start/Stop, programming, cleaning
- EASYLOCK system on the group for a perfect seal with minimal effort
- LED lighting on the group head to illuminate the tray grid
- MAESTRO thermo-regulated brew groups
- Large copper boiler with pressure sensor managing PID temperature control
- Automatic refill with safety and alarm control
- Integrated shot time display
- Groups auto clean programming with back-flush cycles
- USB interface for update
- Includes installation by a Unic certified service provider.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	Aura 2 Group (1011-016)	Two groups with double spouts Medium capacity, 150-200 drinks daily Brews 4 espressos simultaneously	23" X 31" X 24" Height includes 3" stainless steel legs
	Aura 3 Group (1011-017)	Three groups with double spouts Medium capacity, 200-300 drinks daily Brews 6 espressos simultaneously	23" X 39" X 24" Height includes 3" stainless steel legs

TRADITIONAL VOLUMETRIC ESPRESSO MACHINES





Epic Series

Extraordinary Value and Flexibility for a Multi-Boiler Model

Two and Three group multi-boiler precision espresso maker.
This unit is typically operated in mid to high volume cafés.

- Manual or Programmable pressure adjustments during shot preparation
- Central control LCD color touch screen (automatic night/day mode, auto-cleaning, drinks counter, USB interface)
- Capacitive independent touch keypad for each group control boxes with running chronographs
- Adjustable lighting (color/intensity) with 5 to 9 high powered LED RGB per electronic box
- Programmable pre-infusion
 - Time/Pressure – independent per group
- Large cup warmer
- 1 programmable adjustable hot water outlet
- Directly connected to water drain
- Includes installation by a Unic certified service provider.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 Epic - 2 black (1011-024) white (1011-026) stainless (1011-028)	Two groups with multi boiler Small to medium capacity, 100-150 drinks daily Brews 4 espressos simultaneously	23"X 31"X 24" Height includes 3" stainless steel legs
 Epic - 3 black (1011-025) white (1011-029) stainless (1011-031)	Three groups with multi boiler High volume capacity, 200-300 drinks daily Brews 6 espressos simultaneously	23"X 39"X 24" Height includes 3" stainless steel legs

ACCESSORIES

UNIC

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
Base Cabinet (250-00015)	For use with Korinto Prime. Sides of cabinet are black, powder-coated metal, countertop is black Formica.	Height: 32.7" Base Width: 16" Countertop Width: 26" Depth: 20.5"
Mini Fridge (250-00017)	One-gallon Pump Refrigerator Designed to be placed next to an espresso machine, completely insulating and refrigerating a one-gallon container of milk. Built-in hose hole	13.5" x 8.88" x 18"



MODEL	DESCRIPTION
Filter Basket for Single Pods (33406)	Basket holds single, 45mm ESE pods
Filter Basket for Double Pods (33407)	Basket holds pods for double espresso shots
SteamAir - Steam wand (STEAMAIR)	Steam wand w.auto foam auto temp shut-off
Waste Drawer w. Sight Glass - Sgl.Mira (RB-1055)	Fits under unit as a drain
Pod Dual Chamber Adapter (31917)	Per Group - 45mm single pods
Café Accessory Kit (250-00401)	Tamper, Knock Box, Pitchers, Mat
Tango Accessory Kit (250-00393)	(2) shot glasses, (1) 20 oz steam pitcher, (2) 32 oz steam pitchers, (2) stirring spoons, and (2) foam spoons

ACCESSORIES



for Espresso Machines

Tampers

Model	2802-000	2802-001	2802-002	410-00841	LF-LEVEL
Description	PUQPRESS Q2 Black	PUQPRESS Q2 White	PUQPRESS Q1	Unic Basic Tamper 57mm	Unic Distribution Tool 57mm

Barista Tools

Model	E-12OZPITCHER	E-20OZPITCHER	E-32OZPITCHER	KNOCK-LG1
Description	12 Ounce Macchiato Pitcher RW	20 Latte Art Pitcher RW	30 Latte Art Pitcher RW	Knock Box - Stainless - 6" x 4" by Rattleware

Model	E-FSPOON	E-TSPOON	E-2OZSHOT	E-PMAT
Description	Foam Spoon - to dispense cappuccino foam	Twist Spoon - for stirring	Shot Glass - 2 Ounce	Rubber Mat - for Tamping 8" X 6"

Cleaning & Maintenance

Model	URNEX-12-EXP20	92060	URNEX-12-E16-UX100	RB-0100
Description	Urnex Cafiza - 20 Ounce Jar	Tango Detergent Tablets - 120 /jar	Cafiza 1.2gr - 100/jar Cleaner (Pony/DCA)	Pony2 Cleaning Tablet Holder

Model	URNEX-12-RAF32	PA-84B	E-GROUPBRUSH	E-GRINDERBRUSH
Description	Rinza Cleaning Milk Cleaner - 32 oz. (Acid)	Blind Cleaning Filter Basket - 57mm	Pallo Group Brush - for daily brew group basket cleaning	Pallo Grinder Brush - to clean loose grounds

Espresso Machine Water Filtration (3M)

Model	3M-B165-CLS	3M-B195-CLS	3M-BH3-NPT
Description	3M ScaleGard B165- CLS Blend Cartridge	3M ScaleGard B195-CLS Blend Cartridge	3M Blend Head Manifold - 3/8npt - needed with new filter system

AUTOMATIC ESPRESSO MACHINES

UNIC

Korinto Prime Automatic One-Step with Powdered Milk


Barista Quality Drinks at the Push of a Button

Ideal for direct-to-public dispensing, serving up to 100 drinks daily. The user selects the drink they want, and the machine does the rest: doses the beans, grinds them, loads and tamps the portafilter, pulls the extraction using the right water temperature and water volume, and mixes in the milk or other solubles to deliver the completed drink. The machine then ejects the grounds into an internal reservoir, and then runs a quick cleaning cycle on itself so it's ready for the next customer.

No operator skill required, exceptional quality, consistency, and variety of drinks, and the small footprint doesn't take up a lot of space. Profitable addition to any existing beverage program or an easy entry point into the specialty beverage market. Perfect choice for cafeterias, refreshment areas for business, education, hospitals, offices, foodservice, bagel shops, bakeries, and clubhouses.

- 8 programmable drinks
- 7 programmable adjustments for every drink
- Coffee bean hopper and 2 soluble hoppers
- Back-lit, touch sensitive selection panel
- Fits up to 9.45" cups
- Quiet running at <70 dB
- Includes installation by a Unic certified service provider.
(water filter not included)



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	Korinto Prime (1005-003)	(1) 2.1 lbs. (1 kg) coffee bean hopper and (2) soluble hoppers with (1) 20.3 oz (0.6 L) boiler	Machine closed for dispensing: 28.25" x 13" x 21" With upper lid open for refilling: 36.5" x 13" x 21"
	Planned Maintenance Kit	1 Year Schedule	250-00139

INSTALLATION

UNIC

MODEL	DESCRIPTION
Installation Package (80598)	<p>Required for Korinto Prime espresso machines to qualify for factory warranty. The install, start, and adjust program includes limited installation, equipment inspection, equipment start-up, and operator training at a single location 35 miles or less from a Grindmaster Certified Service Provider. This is not barista training.</p> <p>When installation is purchased with a machine, the unit will be shipped to the installer. The customer must provide the following for installation:</p> <ol style="list-style-type: none"> 1. Appropriate electric service within 4 feet of the machine's location for electric hook-up including appropriate heavy duty grounded receptacle with its own breaker. 2. Access to cold water with a minimum of 30 psi pressure with adequate shut-off valve within 6 feet of the machine's location on units requiring water line hook-up. 3. Adequate drain availability for flexible drain hose on units requiring water line hook-up. 4. Adequate and appropriate space to position unit.

WATER TREATMENT*

UNIC



MODEL	FEATURES	PRODUCT DIMENSIONS (h x w x d)
250-00011	Purity C500 Water Filter Starter Kit Complete kit to test water, and adjustable bypass to produce exactly the water you need - minimizing scale, and retaining minerals that benefit taste. NSF Certification.	22" x 6" x 6"
250-00012	Replacement Water Filter Cartridge For Purity C500 water filter. NSF Certification.	19" x 4.5" x 4.5"
60206	Space-saving Water Filter System Includes both water softener and dual-purpose carbon filter in a single mounting system.	14" x 10.5" x 5.25"
60253	Replacement Water Softener Cartridge For use with the 60206 filter system. Reduces mineral build-up that can damage your machine with FDA-grade softener resin. Material: High impact heavy gauge plastic	9.75" H x 2.88" D
63174	External Bottled Water Pump Kit Point-of-Use water pump delivers purified water from a 5-gallon water bottle. For remote locations where water supply is inaccessible.	N/A

* Highly recommended for all espresso machines

ESPRESSO DOSER GRINDERS




UNIC

Doser Delivery Espresso Grinder Models:

A durable and reliable approach to grinding for espresso. The smooth and responsive action of the doser lever movement is much appreciated by the busy barista. Steady Lock step-less grind size adjustment paired with adjustable dosing vanes make these doser espresso grinders the durable and reliable workhorses of the cafe. Each model is also equipped with an asynchronous motor with thermal cut-out to address overheating safety, and sturdy polycarbonate hoppers.

- CDE6x is an efficient space saving commercial model with an timer adjustable from 5 seconds to 1 minute.
- CDE7A automatically keeps the doser chute always full and ready for dispensing as the grinder stops when the doser is full.
- CDE8 is automatic as well and is designed for those high turnover sites, with cooling fans and 83mm burrs for a speedy and consistent delivery.



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	CDE6X (1304-018)	Timer controlled 64mm flat burr dosing grinder with gearless adjustable timer dial Capacity: Up to 200 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	21" X 11" X 7"
	CDE7A (1304-000)	Automatic medium capacity 64mm flat burr dosing grinder Capacity: Up to 200 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	25" X 12" X 9"
	CDE8 (1304-017)	Automatic large capacity 83mm flat burr dosing grinder with cooling fans Capacity: 200 to 300 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	25" X 12" X 9"

ON-DEMAND ESPRESSO GRINDERS







UNIC

On-Demand Espresso Grinders:

Continuing down the path from our doser grinders, improved dose accuracy and product freshness are the keystone features of our on-demand grinder line. Programmable dosing keys and a direct-to-filter path for the ground coffee ensure that the product is always freshly ground and served at its best, while also reducing waste and increasing productivity.

- Each model includes:
- Hands-free operation
- Multi-key touch display controls for an easy programming experience
- The E37S, SL, T, and K all feature the Quick Set Gear for the most easy and precise grind adjustment and the Silent System for low decibel output



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	CDE6P (1304-001)	On-Demand 64mm flat burr grinder with programmable timed grinding with stepless infinitesimal grinding adjustment Capacity: Up to 200 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	23" X 9" X 7"
	CDE37J (Black 1304-002), (White 1304-003)	On-Demand medium capacity 64mm flat burr grinder with programmable timed grinding with stepless infinitesimal grinding adjustment Capacity: Up to 200 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	22" X 12" X 9"
	CDE37S (Black 1304-008), (White 1304-009)	On-Demand large capacity 83mm flat burr grinder with programmable timed grinding with stepless Quick Set Gear grinding adjustment Capacity: Up to 300 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	22" X 12" X 9"
	CDE37SL (Black 1304-015), (White 1304-016)	On-Demand very large capacity 83mm flat burr grinder with programmable timed grinding with stepless Quick Set Gear grinding adjustment and cooling fans Capacity: Up to 500 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	25" X 12" X 9"
	CDE37T (Black 1304-011), (White 1304-012)	On-Demand very large capacity 83mm flat titanium burr grinder with programmable timed grinding with stepless Quick Set Gear grinding adjustment and cooling fans Capacity: Up to 500 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	25" X 12" X 9"
	CDE37K (Black 1304-005), (White 1304-006)	On-Demand very large capacity 71mm Conical burr grinder with programmable timed grinding with stepless Quick Set Gear grinding adjustment and cooling fans Capacity: Up to 500 drinks daily Bean Hopper: 3.5 lbs. (1.6 kg)	25" X 12" X 9"

ESPRESSO GRINDER DOSERS



Venezia Espresso Grinder-Dosers

Precise Control

Heavy-duty, high-torque, direct drive grinder-dosers with infinite grind adjustments and exacting precision. These grinder-dosers allow your shop to make it through a rush without having to stop and grind coffee for each drink.

- VGT offers a timer version: set the timer to start the grind, machine turns off automatically after time is up. Timer can also be stopped manually. 1 minute maximum grind.
- VGA and VGHDA offer automatic versions: doser chute is always kept full, ready for dispensing. Auto starts every 12 doses, the grinder stops when the chute is full.
- Direct drive, 1600 rpm motor.
- Overheating safety protection.
- Dose adjustment: 5.5g - 9g.
- Shot counter on doser indicates the number of cups of espresso that have been served.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
VGT (077800L)	Timer model with 1-minute timer 0.5 hp direct drive motor. 64 mm flat precision stainless steel burrs Capacity: Up to 200 drinks daily Bean Hopper: 2.7 lbs. (1.2 kg) Ground Espresso: 0.6 lbs (250 g)	24" x 9.5" x 16.5"
VGA (077810L)	Automatic model 0.5 hp direct drive motor 64 mm flat precision stainless steel burrs Capacity: Up to 200 drinks daily Bean Hopper: 2.7 lbs. (1.2 kg) Ground Espresso: 0.6 lbs (250 g)	24" x 9.5" x 16.5"
VGHDA (077820L)	Heavy-duty, Automatic Model 1.0 hp direct drive motor 83 mm flat precision stainless steel burrs Built in cooling fan Capacity: Up to 200-300 drinks daily Bean Hopper: 4 lbs. (1.8 kg) Ground Espresso: 0.8 lbs (360 g)	25" x 9.5" x 18"

ESPRESSO GRINDER DOSERS



Venezia II Espresso Grinder-Dosers

Exact Grind

In fast-paced environments, this timer model grinder-doser keeps up with demand so you can concentrate on your customers. Direct drive, 0.5 hp 1550 rpm motor, infinite grind adjustments, and exacting precision let this grinder-doser handle workloads of up to 200 cups a day without taking a coffee break.

- Set the timer to start the grind, machine turns off automatically after time is up. Timer can also be stopped manually. 5 minute maximum grind.
- 64 mm flat specially hardened stainless steel burrs.
- Heavy duty cast aluminum body.
- Overheating safety protection.
- Dose adjustment: 5.5g - 9g.
- Doser quickly and easily fills your espresso machine's portafilter.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
HC-600 (1303-000)	Timer model with 5-minute timer Capacity: Up to 200 daily drinks Bean Hopper: 3 lbs. (1.4 kg) Ground Espresso: 0.6 lbs (250 g)	22" x 7.75" x 11"

ORANGE JUICE MACHINES

Crathco

Automatic Efficiency and Juicy

Quick, Efficient, and Juicy


The exclusive design of the juicer separates the peel from the pulp, so that it is not pressed during the squeezing process. The peel never touches the juice, ensuring sanitation.

- Micro-serrated slicing blade - heavy-duty stainless steel blade strong enough to quickly slice through the thickest peel.
- Available carousel-style automatic feeder - fruit is automatically fed into the machine quickly and efficiently as the feeder rotates.
- Fruit Diameter: 2.36" - 3.2"




Countertop Model



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 JX15MC (095500L)	Orange color, manual feed Feed rate: 15 oranges per minute Feeder capacity: 6 oranges 120V / 1.08 kW / 9A / 1 Ph NEMA 5-15P line cord included.	33" x 19.5" x 19.75"
Planned Maintenance Kit	1 Year Schedule	250-00168

Floor Model



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 JX45AF (095555L)	Orange color, auto feed, juice reservoir, and self-serve faucet. Feed rate: 45 oranges per minute Feeder capacity: 39 lbs. 120V / 1.08 kW / 9A / 1 Ph NEMA 5-15P line cord included.	71.5" x 23" x 29.5"
Planned Maintenance Kit	1 Year Schedule	250-00169

COLD BEVERAGE DISPENSERS

Crathco

PREMIX Simplicity® Bubblers®

Sleek Design

Dispense up to four flavors in 2.4 or 4.75 gallon clear plastic bowls on a stainless steel base with 9" cup clearance.



Agitator Models

Choose the minimal foaming system in the agitator model and pair it with our BPA free bowl assembly kit.



Interchangeable Bowls

Different size bowls fit the same machine!

Easily convert your Simplicity Bubbler to the best bowl configuration for your needs.

Wherever you have two 2.4 gallon bowls on a Simplicity base, you can replace them with a 4.75 gallon bowl and vice versa.

Note: The Triple Tall Models (CS-3L Series) are not interchangeable.

COLD BEVERAGE DISPENSERS

Crathco

PREMIX
Simplicity® Bubblers®



Reduced Maintenance

Fewer removable parts also means less maintenance and a longer lifetime.



Dispense Levers

Dispense levers can be removed quickly and easily without affecting the product dispense valves.



Easy and Better Sealing

Advanced sealing guards against leakage, providing trouble-free usage.

COLD BEVERAGE DISPENSERS

Crathco







PREMIX Simplicity® Bubblers®

Less Equals More

Simplicity pre-mix dispensers are the first machines that are proud to offer less. Less counter space with their compact size. Less time and effort in cleaning and disassembly. Less wear and power usage. Less waste, with product dispensed to the last drop. Less worry with fewer removable parts. And, less maintenance. Which we believe gives you much, much more.

- Pre-mix dispenser with stainless steel base and clear plastic easy-clean bowls.
- Unique to Simplicity more efficient front-to-back air circulation. Efficient cooling uses less energy and saves money.
- New easy-off bowl release system for faster and easier assembly and disassembly.
- Design enables machine to dispense product until the very last drop.
- Fewer removable parts to simplify cleaning and reduce maintenance, including removable tray.
- 9" cup clearance for a variety of drinks.
- Temperature range from 35 - 41°F.
- BPA Free Bowl options available.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	MINI TWIN MODELS	CS-2E-16 Base: 231-00001 Standard Bowl Set: 231-00539 BPA-Free Bowl Set: 231-00672	(2) 2.4 gallon bowls 27.5" x 10.5" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00120
	MINI QUAD MODELS	CS-4E-16 Base: 231-00234 Standard Bowl Set: 231-00543 BPA-Free Bowl Set: 231-00674	(4) 2.4 gallon bowls 27.5" x 20.5" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00122
	SINGLE STANDARD BOWL MODELS	CS-1D-16 Base: 231-00001 Standard Bowl Set: 231-00541 BPA-Free Bowl Set: 231-00673	(1) 4.75 gallon bowl 27.5" x 10.5" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00124
	TWIN STANDARD BOWL MODELS	CS-2D-16 Base: 231-00234 Standard Bowl Set: 231-00545 BPA-Free Bowl Set: 231-00675	(2) 4.75 gallon bowls 27.5" x 20.5" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00126
	TRIPLE TALL BOWL MODELS	CS-3L-16 Base: 231-00426 Standard Bowl Set: 231-00549 BPA-Free Bowl Set: 231-00677	(3) 4.75 gallon bowls 31.3" x 20.4" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00130
	TRIPLE COMBO BOWL MODELS	CS-3D-16 Base: 231-00234 Standard Bowl Set: 231-00547 BPA-Free Bowl Set: 231-00676	(1) 4.75 gallon bowl and (2) 2.4 gallon bowls 27.5" x 20.5" x 17.75" Height includes 4" legs
Planned Maintenance Kit		Six Month Schedule	250-00128

OPTIONS & ACCESSORIES

Crathco

PREMIX Simplicity® Bubblers®

Model	231-00227	231-00293	210-00118
Description	Merchandiser Kit for Mini Twin and Single Bowl Models Attract customers with extra graphics.	Merchandiser Kit for Mini Quad and Double Bowl Models Attract customers with extra graphics.	Condenser Filter Protect your condenser with a simple, easy to clean filter. 8.25" x 3.25. For use with CS-2E-16 and CS-1D-16 models only.

Model	210-00585	250-000354
Description	Protect your condenser with a simple, easy to clean filter. For use with models CS-4E-16, CS-2D-16, CS-3D-16, and CS-3L-16	Crathco Clearly Clean Kit Use fewer products and less water while saving cleaning time with the only manufacturer-approved cleaning system for your Crathco Bubblers, including Crathco Simplicity, Crathco Classic, and Crathco G-Cool. You can clean your equipment easily without disassembly between regular required cleaning and sanitizing as detailed in the operator manual. Keep your bowls clean and clear to properly display your product. Kit includes: 50/1 oz packets of Stera-Sheen Green Label Sanitizer and Cleaner, 1-gallon shaker jug, multipurpose soft-bristled brush, laminated recommended procedures

COLD BEVERAGE DISPENSERS

Crathco

PREMIX

Classic Bubblers®

Durable and Efficient


Keep a steady supply of cold drinks on hand with Crathco Classic Bubbler cold beverage dispensers. Stainless steel and super-strong, virtually unbreakable bowls and covers ensure long-lasting use, and are easy to maintain for a fast, simple cleanup. Crystal-clear bowls and covers showcase your colorful signature fruit juice, tea, and iced coffees and provide an eye-catching appearance - perfect for boosting impulse sales.

- Unique evaporator and high efficiency pump cools faster and more efficiently for quick start-up.
- Along with spray circulation, agitators are included with each unit for fresh juices, coffees, or tea.
- Superior engineering allows full beverage cooling to the dispense point, and right down to the last drink.
- Bowls have easy-to-read measuring marks and models with more than one bowl separate to allow cleaning and flavor changes without total system shut-down.
- Temperature range from 35 - 41°F.





Standard Series



MODEL			DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	SINGLE 5-GALLON BOWL MODELS	Stainless Steel Side Panels and Drip Tray D15-3; Base: (5619) Bowl: (5111)	1 bowl, Certified NSF / ANSI 20- safe for milk, 8.25" cup clearance.	27.25" x 10.25" x 16"
	Planned Maintenance Kit Six Month Schedule 250-00136	Plastic Side Panels and Drip Tray D15-4; Base: (5619) Bowl: (5111)		
	DOUBLE 5-GALLON BOWL MODELS	Stainless Steel Side Panels and Drip Tray D25-3; Base: (5507) Bowl: (5112)	2 bowls, 8.25" cup clearance.	27.25" x 17.5" x 16"
	Planned Maintenance Kit Six Month Schedule 250-00138	Plastic Side Panels and Drip Tray D25-4; Base: (5508) Bowl: (5122)		
	TRIPLE 5-GALLON BOWL MODELS	Stainless Steel Side Panels and Drip Tray D35-3; Base: (5511) Bowl: (5113)	3 bowls, 8.25" cup clearance.	27.25" x 25.75" x 16"
	Planned Maintenance Kit Six Month Schedule 250-00140	Plastic Side Panels and Drip Tray D35-4; Base: (5512) Bowl: (5123)		

Mini Bowl Series



MODEL			DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	DOUBLE 2.4-GALLON BOWL MODELS	Stainless Steel Side Panels and Drip Tray E29-3; Base: (5584) Bowl: (5114)	2 bowls, 8" cup clearance.	25.5" x 11.25" x 16"
	Planned Maintenance Kit Six Month Schedule 250-00142	Plastic Side Panels and Drip Tray E29-4; Base: (5583) Bowl: (5124)		
	QUAD 2.4-GALLON BOWL MODELS	Stainless Steel Side Panels and Drip Tray E49-3; Base: (5538) Bowl: (5115)	4 bowls, 8" cup clearance.	27.25" x 17.5" x 16"
	Planned Maintenance Kit Six Month Schedule 250-00144	Plastic Side Panels and Drip Tray E49-4; Base: (5542) Bowl: (5125)		

OPTIONS & ACCESSORIES

Crathco

PREMIX

Crathco® Classic Bubblers®

Model	3587	3709
Description	Standard MCX Mag Drive™ Impeller (black) For juices and water.	MCX Mag Drive™ Low Foam Impeller (black with blue center) For products that create foam, such as teas and lemonades.
Product Dimensions	2" Diameter	2" Diameter

Model	3657	2039	2502
Description	Condensation Cover For use with D15, D25, D35. Direct and conceal condensation in high humidity or outdoor locations.	Valve Cap Improves sealing of valve when using pulpy product.	Valve Locking Box For use with cup activated handle - cannot be used with non-contact handle. Secures the valve from dispensing during off-hours.
Product Dimensions (H x W x D)	10" x 7.5" x 3.25"	1.75" Diameter	6" x 3.5" x 3.25"

Model	2484	2266	2543
Description	Non Contact Handle (Standard)	Cup Activated Handle	3" Legs Set of 4
Product Dimensions (H x W x D)	4.25" x 3.25" x 1"	5.25" x 3.25" x 3"	0.5" Diameter

Model	2509	2510	2511	5353
Description	Security Kit For use with D15	Security Kit For use with D25	Security Kit For use with D35	Security Kit For use with E49

Model	5925
Description	Shipboard Kit For use with D15, D25, D35. Only available for use with agitator. Makes unit safer for installation aboard marine vessel.

COLD BEVERAGE DISPENSERS

Crathco

PREMIX

Crathco® G-Cool® Series

So Many Options – Even Safe for Milk!

The most advanced, user-friendly cold premix dispenser available, for up to 4 flavors with options of both 2.4 and 5 gallon bowls. Easy operator interface, simple machine care, and faster cleaning. Cleans in half the time of a traditional dispenser. Patented Tri-Cool™ evaporator with a large 3-sided cooling surface refrigerates through the bowl using less energy and saving money.



Low aeration magnetic mixing system keeps product mixed without creating unwanted foam in tea and cappuccino products.

- 360° merchandising with choice of fruit, tea, or cappuccino graphic attract customers.
- Stainless steel dispensing valve and 9.5" cup height.
- Temperature range from 35 - 41°F.
- Certified NSF / ANSI 20 - safe for milk.




5-Gallon Bowl Models

NSF-20  

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 C-1S-16 (231-00162) Planned Maintenance Kit Six Month Schedule 250-00132	(1) 5 gallon bowl	26.5" x 12.5" x 19.5"
 C-2D-16 (231-00166) Planned Maintenance Kit Six Month Schedule 250-00133	(2) 5 gallon bowls	26.5" x 22" x 19.5"



Focus Flavor Models

NSF-20  

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 C-3D-16 (231-00168) Planned Maintenance Kit Six Month Schedule 250-00134	(1) 5 gallon bowl and (2) 2.4 gallon bowls	26.5" x 22" x 19.5"

Mini Models

NSF-20  

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 C-2S-16 (231-00164) Planned Maintenance Kit Six Month Schedule 250-00133	(2) 2.4 gallon bowls	26.5" x 12.5" x 19.5"
 C-4D-16 (231-00170) Planned Maintenance Kit Six Month Schedule 250-00135	(4) 2.4 gallon bowls	26.5" x 22" x 19.5"

Specify Graphic: Iced Coffee (99454), Iced Tea (99455), or Fruit (99456)

OPTIONS & ACCESSORIES

Crathco

PREMIX
Crathco® G-Cool® Series

Model	99453	99634
Description	Single cradle 4" leg kit (Optional on single units, standard on double cradle units)	Heavy valve assembly for G-Cool for use with products with pulp 3.8" H x 1.45"

FROZEN GRANITA DISPENSERS

Crathco

I-Pro 2 & 3 Frozen Granita Dispensers

Introducing the most advanced professional slush, sorbet, and granita machine in the world. Even safe for milk!



High performance, ultramodern design, and user-friendly. Insulating technology increases cooling power, saves energy and money, and reduces external condensation. Choose from either (2) or (3) 2.9 gallon insulated bowls with either mechanical or electronic control board and timer, and optional light panel.

Perfect solution for restaurants, coffee shops, bars, amusement parks, convenience stores, kiosks, and much more.

- All models are certified NSF-6 safe for milk.
- Transparent bowl encourages impulse purchasing.
- Manual defrost mode.
- Efficient safety mechanism is activated when cover is lifted. All moving parts automatically and immediately stop.
- Lockable lid.
- Adjustable product consistency.
- Black finish.
- Commercial grade parts ensure a long life in heavy-usage locations.
- Repairable machine with available replacement parts.





I-Pro 2 Frozen Granita Dispensers



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
I-PRO 2M (1206-000)		(2) 2.9 gallon insulated bowls, Mechanical control and timer.	34" x 16" x 23"
	I-PRO 2M light panel (1206-001)	(2) 2.9 gallon insulated bowls, Mechanical control and timer, Lighted panel.	34" x 16" x 23"
	I-PRO 2E (1206-002)	(2) 2.9 gallon insulated bowls, Electronic control and timer.	34" x 16" x 23"
I-PRO 2E light panel (1206-003)		(2) 2.9 gallon insulated bowls, Electronic control and timer, Lighted panel.	34" x 16" x 23"
Planned Maintenance Kit		1 Year Schedule	250-00301

I-Pro 3 Frozen Granita Dispensers



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	I-PRO 3M (1206-004)	(3) 2.9 gallon insulated bowls, Mechanical control and timer	34" x 24" x 23"
	I-PRO 3M light panel (1206-005)	(3) 2.9 gallon insulated bowls, Mechanical control and timer, Lighted panel	34" x 24" x 23"
	I-PRO 3E (1206-006)	(3) 2.9 gallon insulated bowls, Electronic control and timer	34" x 24" x 23"
	I-PRO 3E light panel (1206-007)	(3) 2.9 gallon insulated bowls, Electronic control and timer, Lighted panel	34" x 24" x 23"
Planned Maintenance Kit		1 Year Schedule	250-00302

Note: Operate at room temperature between 75 - 90° F.
Note: Mixture must maintain a sugar content near 14%.

FROZEN GRANITA DISPENSERS

Crathco

Frosty Frozen Granita Dispensers


Perfect for Indoor or Outdoor Use

Frosty Frozen Dispensers are the go-to model when you want large-sized, high-performance equipment, without a high investment. Slushes, sherbets, and other frozen treats are created with a double mixing system that prevents ice accumulation, for optimum product consistency that is also adjustable. The black and stainless steel finishes and illuminated lid encourage impulse purchasing.

- Efficient safety mechanism is activated when cover is lifted. All moving parts automatically and immediately stop.
- All models are certified NSF-6 safe for milk.
- LED illumination system.
- Manual control keypad.



NSF-6
ETL Intertek ETL Intertek

MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	Frosty 2 (1206-010)	(2) 3.2 gallon tanks, 6.3 gallon total capacity	32.5" x 15.8" x 21.9"
Planned Maintenance Kit		1 Year Schedule	250-00305
	Frosty 3 (1206-011)	(3) 3.2 gallon tanks, 9.5 gallon total capacity	32.5" x 23.6" x 21.9"
Planned Maintenance Kit		1 Year Schedule	250-00306

Note: Operate at room temperature between 75 - 90° F.
 Note: Mixture must maintain a sugar content between 12-14%; a lower concentration could seriously damage the mixing parts and gear motors.

BARREL FREEZERS

Crathco


MP Series Crathco® Single Barrel Freezers

High-Volume, High-Demand

You won't come across another slush machine that is so user-friendly! Provides continuous, rapid production, thanks to its gravity-feed system.

- 4.76 gallon capacity single barrel freezer.
- Certified NSF-6 safe for milk.
- Front window ensuring product visibility, and encourages impulse purchasing.
- Refrigerated tank.
- LED-illuminated graphic panel for customer appeal.
- Robust stainless steel structure.
- Mechanical control board and defrost mode.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	MP (1207-000)	2.64 gallons capacity in hopper, 2.1 gallons capacity in cooling cylinder	31" x 14" x 28"
Planned Maintenance Kit		1 Year Schedule	250-00310

Note: Operate at room temperature between 75 - 90° F.
Note: Mixture must maintain a sugar content between 12-14%; a lower concentration could seriously damage the mixing parts and gear motors.

BARREL FREEZERS

Crathco

3000 & 5000 Series Crathco® Barrel Freezers

Industry Workhorse

Serves a variety of frozen smoothies, frozen cappuccinos or lattés, granitas, frozen fruit juices, frozen lemonades, slushes, or cocktails. Your delicious drinks are continually replenished in the barrel by a large product reservoir, and a mix low light alerts you when the reservoir needs to be refilled. Patented FlavorLight™ illuminates your beverage with your choice of eye catching back-lit signs that draw customers and increase sales.

The oversize drive motor, sturdy belt drive, and heavy-duty stainless steel frame construction will stand tough against years of high volume use. Individual controls allow you select on/off, clean, and mix out for each barrel so you can easily maintain your machine for consistent dispensing and long life.


This space-saving unit is great for self-serve applications or behind-the-bar service, providing you with everything you need to serve a variety of delicious frozen treats!

- Heavy-duty components provide lasting commercial use.
- Compact units provide big service.
- Mechanical control in the 3000 Series.
- Electronic control in the 5000 Series.




3000 Series



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 3312 (CFB3312-A)	Twin barrel, (2) 0.25 hp drive motors	28.5" x 18.5" x 29"
Planned Maintenance Kit	1 Year Schedule	250-00116

5000 Series



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 5711 (CFB5711-B)	Single barrel, 0.5 hp drive motor	28.5" x 18.5" x 29"
Planned Maintenance Kit	1 Year Schedule	250-00119

ACCESSORIES

Crathco

Crathco® Barrel Freezers

Model	W0890208	W0890200	W0890206	W0890220
Description	Concealed Filter Kit Black	Concealed Filter Kit Stainless Steel	Exposed Filter Kit	Legs Set of (4)

Model	W0470051
Description	Refractometer

Start and Adjust for Counter Models

Model	W0910001 Start and Adjust, Single Barrel	W0910002 Start and Adjust, Twin Barrel
Description	<p>Start and Adjust available for all counter units except remote condensing or pressurized models. The Install, Start, and Adjust Program includes limited installation, equipment inspection, equipment start-up, and operator training at a single location 35 miles or less from a Grindmaster Authorized Service Center.</p> <p>When installation is purchased with a machine, the unit will be shipped to the installer. The customer must provide the following for installation:</p> <ol style="list-style-type: none"> 1. Appropriate electric service within 4 feet of the machine's location for electric hook-up including appropriate heavy duty grounded receptacle with its own breaker. 2. Access to cold water with a minimum of 30 psi pressure with adequate shut-off valve within 6 feet of the machine's location on units requiring water line hook-up. 3. Adequate and appropriate space to position unit 	

FROZEN GRANITA & COLD CREAM DISPENSERS

Crathco

SP Series


Cold Cream and Frozen Coffee

One compact counter machine creates both chilled beverages like frozen coffee, fruit juices, frozen cocktails, and creamy desserts, like mousses, cold creams, slushes, sherbets, and sorbets. Functions with both water or milk added to dried base or with ready-to-use mixed product bases to create delicious chilled treats. Easy to clean and user-friendly, this is the perfect solution for restaurants, cafeterias, coffee shops, bars, or hotels.

- Easy disassemble without tools for cleaning.
- Lockable lid.
- Mechanical control board.
- Manual defrost mode.
- Digital display shows the bowls temperature.
- All models are certified NSF-6 safe for milk.



NSF-6  

MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
SP 1 (1206-008)		(1) 1.3 gallon capacity	24" x 10" x 17"
Planned Maintenance Kit		1 Year Schedule	250-00303
	SP 2 (1206-009)	(2) 1.3 gallon capacity, 2.6 gallon total capacity.	24" x 18" x 17"
Planned Maintenance Kit		1 Year Schedule	250-00304

FROZEN DESSERTS & COLD CREAM DISPENSERS

Crathco

GT Push Frozen Desserts Dispensers


Easy Freeze

Elegant appearance, small footprint, versatile, and delicious! This compact, multi-purpose wonder creates the perfect thick shakes, soft serve, slushes, smoothies, sherbets, frozen yogurts, frozen fruit drinks and frozen coffees, or whatever your own signature frozen specialty may be!

The GT Push is simple, easy, and reliable, designed to operate with either water or milk-based products to create delicious chilled specialties.

- Transparent bowl and clean white finish encourage impulse purchasing.
- Efficient safety mechanism is activated when cover is lifted. All moving parts automatically and immediately stop.
- LED-based electronic keypad.
- When the product is ready, just press the push button, increasing motor speed, and allowing quicker dispensing.
- All models are certified NSF-6 safe for milk.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
GT Push 1 (1206-012)		(1) 1.3 gallon insulated tank	26" x 10" x 17"
Planned Maintenance Kit		1 Year Schedule	250-00307
	GT Push 2 (1206-013)	(2) 1.3 gallon insulated tanks, 2.6 gallon total capacity	26" x 18" x 17"
Planned Maintenance Kit		1 Year Schedule	250-00308

ICE CREAM DISPENSERS

Crathco

Karma Soft Ice Cream Dispensers

Ice Cream Cones in 24 Seconds

Delicious soft serve ice cream and frozen yogurt in a compact, quiet, counter-top machine! Its cooled hopper reduces dispense time, as the product is cold before reaching the freezing cylinder. And, don't let the small size fool you. The Karma gives back to the universe by producing 150 ice cream cones an hour!

- Auto defrost/night mode: keeps product fresh.
- Product is ready in a few minutes after start-up.
- Minimum level warning light.
- Customizable dispensing lever.
- 3 consistency levels.
- Certified NSF-6 safe for milk.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
Karma Gravity (1208-002)	1.85 gallon capacity in cooled upper tank, 0.61 gallon capacity in freezing cylinder, 2.5 gallon total capacity Production Capacity: 20 lbs. per hour - about 150 cones	25.5" x 14.1" x 20.5"
Planned Maintenance Kit	1 Year Schedule	250-00312
Karma Pump (1208-003)	1.85 gallon (7.0 L) capacity in cooled upper tank, 0.61 gallon (2.3 L) capacity in freezing cylinder, 2.5 gallon (9.3 L) total capacity Production Capacity: 20 lbs. per hour - about 150 cones	25.9" x 14.1" x 20.5"

ICE CREAM DISPENSERS



K-Soft Ice Cream Dispensers

Ice Cream Cones in 24 Seconds

Delicious soft serve ice cream and frozen yogurt in a compact, quiet, counter-top machine! Its cooled hopper reduces dispense time, as the product is cold before reaching the freezing cylinder. And, don't let the small size fool you. The K-Soft gives back to the universe by producing 150 ice cream cones an hour!

- Perfect for users who want to enter soft ice cream market without investing in industrial, oversized equipment.
- Compact counter-top unit, ideal for small spaces.
- Simple, practical, quiet, and reliable.
- Production capacity of 11 lbs. (5 kg) per hour.
- Excellent capacity: 0.92 gallon (3.5 L) in cooled upper tank, and 0.26 gallon (1 L) in freezing cylinder, for a total capacity of 1.2 gallon (4.5 L).
- Air cooling.
- Certified NSF-6 safe for milk.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
K-Soft (1208-000)	0.92 gallon capacity in cooled upper tank, 0.26 gallon capacity in freezing cylinder, 1.2 gallon total capacity Production Capacity: 11 lbs. per hour - about 150 cones	27.6" x 9.4" x 22.8"
Planned Maintenance Kit	1 Year Schedule	250-00311

COOKING EQUIPMENT



Floor Model Gas Fryers

40, 50, 70 lbs

Sleek and Solid

Constructed of heavy-duty stainless steel for long life and easy maintenance, the new Cecilware Pro line of gas floor fryers are built using the best components the industry has to offer. Offering heavy-duty construction at value prices, these tube fryers are ideal for heavy volume restaurants. The deep cold zone meets the demand for healthier foods by preventing the breakdown of oil, and maximizes savings by prolonging oil life span.

Equipped with multiple safety features, and available in either natural or LP gas, with Invensys® thermostat rated at 200 - 400° F, and an auto reset high limit, these fryers also make the job simple!

- Models available using natural or LP gas.
- 6" adjustable legs.
- Two nickel chrome wire mesh fry baskets included.
- Fry pot depth of 30.25".



40 lb Capacity Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
FMS403LP (555700)	Stainless steel front and galvanized sides, (3) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 15.5" x 30.25" Working Height: 36.25"
FMS403NAT (555710)	Stainless steel front and galvanized sides, (3) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 15.5" x 30.25" Working Height: 36.25"


50 lbs Capacity Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
FMS504LP (555720)	Stainless steel front and sides, (4) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 15.5" x 30.25" Working Height: 36.25"
FMS504NAT (555730)	Stainless steel front and sides, (4) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 15.5" x 30.25" Working Height: 36.25"

70 lbs Capacity Models



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 FMS705LP (555740)	Stainless steel front and sides, (5) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 21" x 30.25" Working Height: 36.25"
FMS705NAT (555750)	Stainless steel front and sides, (5) 30,000 BTU tubes. Gas Inlet Size: 1/2"	48.25" x 21" x 30.25" Working Height: 36.25"

Optional Casters for FMS Model Fryers

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
410-00190	Set of 4 Casters: 2 locking casters and 2 regular casters	5.75" Height, 5" Diameter Wheel

FRYERS

Cecilware[®]
PRO

Floor Model Fryers Baskets

Fryer Baskets with Plasticized Handles

Fry baskets ensure complete and even circulation of shortening for perfect deep fried foods.

- Constructed of sturdy, heavy-gauge wire handles and frames, plus quality nickel-plated wire.



MODEL	FOR USE WITH FRYERS
410-00212	FMS705LP, FMS705NAT

ACCESSORIES

Cecilware[®]
PRO

Floor Model Fryers Accessories

Fryer Covers

Model	U589Q	U641Q
Description	Cover for 40 lbs. fryer	Cover for 65 lbs. fryer
Product Dimensions (H x W x D)	0.75" x 23" x 15.75"	0.75" x 15.75" x 22.81"

Banking Strips

Model	U631A	U633A-L
Description	Banking (connecting) strip 40 lbs. fryer	Banking (connecting) strip 65 lbs. fryer
Product Dimensions (H x W x D)	22.75" x 2.25" x 1"	29.75" x 2.09" x 1.67"

Other Accessories for Fryers

Model	250-00052	V109A
Description	Set of 4 Casters (2 locking and 2 regular casters) For EFS floor model fryers	Standard 200 Pan (for dump station)
Product Dimensions (H x W x D)	5.75" Height 5" Diameter Wheel	2.5" x 21" x 12.75"





Countertop Electric Fryers

Safety and Ease

Easy-to-use controls, all stainless steel construction, and fast-responding heating elements for accurate heat adjustments will have you looking for things to fry up! The stainless steel tank is removable for easy cleaning, and for the best operator safety, thermal overload device turns off the fryer if the heating element gets too hot, and a cutout switch automatically turns off the element when the tank is being removed.

- Includes fry basket(s).
- Non-slip feet.



MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
 EL6 (721140)	(1) 6 lbs. fry pot with (1) basket 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	12.75" x 7.5" x 17.5"
 EL15 (721160)	(1) 15 lbs. fry pot with (2) baskets 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	15.75" x 11" x 17.5"
 EL25 (721180)	(1) 15 lbs. fry pot with (2) baskets 240V / 3.2 kW / 15A / 1 Ph NEMA 6-20P line cord included.	15.75" x 11" x 17.5"
 EL2X6 (721100)	(2) 6 lbs. fry pots with (2) baskets (2) 120V / 1.8 kW / 15A / 1 Ph (2) NEMA 5-15P line cords included.	12.75" x 14.5" x 17.5"
EL2X15 (721120)	(2) 15 lbs. fry pots with (4) baskets (2) 120V / 1.8 kW / 15A / 1 Ph (2) NEMA 5-15P line cords included.	15.75" x 21.75" x 17.5"
EL2X25 (721130)	(2) 15 lbs. fry pots with (4) baskets (2) 240V / 3.2 kW / 15A / 1 Ph (2) NEMA 6-20P line cords included.	15.75" x 21.75" x 17.5"

ACCESSORIES

Cecilware®
PRO

Countertop Fryers Baskets & Accessories

Countertop Fryer Baskets with Back Hook Placement

Model	08050L	08086L	08021L
Description	Single large fry basket	Single large fry basket	Twin fry basket
Fits Fryer Model	EL6 and EL2X6	EL15, EL25, EL2X15, and EL2X25	EL15, EL25, EL2X15, and EL2X25
Ship Weight	2 lbs.	3 lbs.	2 lbs.

Fry Tank Covers

Model	08049L	08020QL
Description	Single fry tank cover	Single fry tank cover
Fits Fryer Model	EL6 and EL2X6	EL15, EL25, EL2X6, EL2X15, and EL2X25
Ship Weight	1.5 lbs.	3 lbs.

GRIDDLES



Medium Duty Gas Griddles

Professional Results

The ultimate in flexibility for your kitchen! Available in four widths with manually controlled, independent cooking zones and a polished steel cooking surface for the best results in grilling.

- All models can be operated using natural or LP gas. Models ship as natural gas unit with no additional parts necessary for conversion.
- Griddle plate thickness of 1" for better heat retention, faster recovery, and more even heat distribution than thin plates.
- Heavy-duty stainless steel full-cooking depth dual-ported burners for long life and easy maintenance.
- Manually controlled, independent cooking zones.
- Bottom-welded plate for accurate heat distribution.
- Non-welded top plate ensures uniform temperature consistency on cooking surface.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	GCP15 (6601-1000)	Cooking surface: 15" W x 20" D BTUs per Hour: 30,000	15.75" x 15.5" x 30"
	GCP24 (6601-1001)	Cooking surface: 24" W x 20" D BTUs per Hour: 60,000	15.75" x 24.5" x 30"
	GCP36 (6601-1002)	Cooking surface: 36" W x 20" D BTUs per Hour: 90,000	15.75" x 36.5" x 30"
	GCP48 (6601-1003)	Cooking surface: 48" W x 20" D BTUs per Hour: 120,000	15.75" x 48.5" x 30"

NOTE: Gas inlet size - 3/4"

GRIDDLES



Thermostatic Gas Griddles

Exact Temperature

Unlike manual griddles that only have temperature ranges, thermostatic griddles can be set to an exact temperature, and will maintain that temperature within a couple of degrees.

- All models can be operated using natural or LP gas. Models ship as natural gas unit with no additional parts necessary for conversion.
- Griddle plate thickness of 1" for better heat retention, faster recovery, and more even heat distribution than thin plates.
- Heavy-duty stainless steel full-cooking depth dual-ported burners for long life and easy maintenance.
- Manually controlled, independent cooking zones.
- One U-shaped burner and thermostat control for every 12" of cooking surface to maintain even heating.
- Throttling thermostat provides a consistent surface temperature and superior food quality.
- Non-welded top plate ensures uniform temperature consistency on cooking surface.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
CE-G15TPF (6602-10000)		Cooking surface: 15" W x 20" D BTUs per Hour: 30,000	15.6" x 15" x 30"
	CE-G24TPF (6602-10001)	Cooking surface: 24" W x 20" D BTUs per Hour: 30,000	15.6" x 24" x 30"
CE-G36TPF (6602-10002)		Cooking surface: 36" W x 20" D BTUs per Hour: 90,000	15.6" x 36" x 30"
CE-G48TPF (6602-10003)		Cooking surface: 48" W x 20" D BTUs per Hour: 120,000	15.6" x 48" x 30"

NOTE: Gas inlet size - 3/4"

GRIDDLES




Medium Duty Electric Griddles

Precise Temperature Control

This countertop griddle provides the heating power you need to produce great results while maintaining a small footprint. Delivering uniform heating without hot spots, temperature is controlled by precision thermostats with pilot light indicator.

- Stainless steel body construction.
- Steel cooking surface.
- Concealed, easily cleaned, removable grease tray and convenient rotary controls for precise temperature control up to 572°F.
- 24" x 16" cooking area.
- 1/2" thick machine polished steel griddle plate.
- Welded, stainless steel splash guards.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	EL1624 (721250)	1 heating element, 1/2" griddle plate thickness 240V / 2.4 kW / 10A / 1 Ph NEMA 6-20P line cord included.	8" x 24" x 16"
	EL1636 (721275)	2 heating elements, 1/2" griddle plate thickness 240V / 3.6 kW / 15A / 1 Ph NEMA 6-20P line cord included.	8" x 36" x 16"

CHARBROILERS

Cecilware[®]
PRO





Gas Charbroilers

Flexibility and Performance

The ideal option for the increasing demand of char grilled food. With reversible, heavy-duty cast iron grilling grates for delicate proteins, manually controlled, independent cooking zones, and grates designed to be tilted for different level heating. Available in four widths, and can alternate between lava rock and radiant cooking methods.

- All models can be operated using natural or LP gas. Models ship as natural gas unit with no additional parts necessary for conversion.
- Stainless steel construction for long life and easy maintenance.
- Angled sidewalls and bottom plate reflect heat into cooking zone for better and more accurate heat distribution.
- Lava Rock Kit and Holding Rack options available in 24", 36", and 48".



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	CCP15 (6600-1000)	(1) burner, 3" & 6" wide grates BTUs per Hour: 40,000	15.75" x 15.5" x 26.5"
	CCP24 (6600-1001)	(2) burners, 6" wide grates BTUs per Hour: 80,000	15.75" x 24.5" x 31.5"
	CCP36 (6600-1002)	(3) burners, 6" wide grates BTUs per Hour: 120,000	15.75" x 36.5" x 31.5"
	CCP48 (6600-1003)	(4) burners, 6" wide grates BTUs per Hour: 160,000	15.75" x 48.5" x 31.5"

NOTE: Gas inlet size - 3/4"

Options

MODEL	DESCRIPTION
250-00031	Lava rocks and holding racks kit for CCP24
250-00032	Lava rocks and holding racks kit for CCP36
250-00033	Lava rocks and holding racks kit for CCP48

HOT PLATES

Cecilware®
PRO



Gas Hot Plates

Heavy-Duty Workhorse

Easily expand your menu offerings! Available in 2, 4, and 6 burner configurations with individually controlled burners, each with 22,000 BTUs per hour. Heavy-duty cast iron trivets create a sturdy work surface.

- All models can be operated using natural or LP gas. Models ship as natural gas unit with no additional parts necessary for conversion.
- Sleek, durable stainless steel construction for long life and easy maintenance.
- Easy access front panel pilot adjustments.
- Durable anti-clogging dual-ported burners.
- Removable grease drawer.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
HPCP212 (6200-1000)		(2) burners. Cooking surface: 12" W x 20" D BTUs per Hour: 44,000	15" x 12" x 27.5"
	HPCP424 (6200-4000)	(4) burners. Cooking surface: 24" W x 20" D BTUs per Hour: 88,000	13.5" x 24" x 30.5"
	HPCP636 (6200-6000)	(6) burners. 36" W x 20" D BTUs per Hour: 132,000	13.5" x 36" x 30.5"

NOTE: Gas inlet size - 3/4"

PANINI GRILLS

Cecilware®
PRO




Sandwich or Panini Grills

What a Time Saver!

Cut your cooking time in half when you cook both sides of a sandwich, hamburger, chicken breast, and many other products simultaneously! The self-balanced top surface adjusts to different heights ensuring even cooking of food.

- Choice of flat or grooved surface.
- Stainless steel construction.
- Cast iron cooking surface.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	SG1SG (721300)	Single, grooved surface. Work surface: 9.6" W x 9" D 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	22" x 15.5" x 15.5" Height with Lid Open: 23.5"
	SG1SF (721315)	Single, flat surface. Work surface: 9.6" W x 9" D 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	22" x 15.5" x 15.5" Height with Lid Open: 23.5"
	SG1LG (721325)	Single plus, grooved surface. Work surface: 14" W x 11" D 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	22" x 20.25" x 17.5" Height with Lid Open: 23.5"
	SG1LF (721350)	Single plus, flat surface. Work surface: 14" W x 11" D 120V / 1.8 kW / 15A / 1 Ph NEMA 5-15P line cord included.	22" x 20.25" x 17.5" Height with Lid Open: 23.5"
	SG1LG24 (721320)	Single plus, grooved surface. Work surface: 14" W x 11" D 240V / 2.4 kW / 10A / 1 Ph NEMA 6-20P line cord included.	22" x 20.25" x 17.5" Height with Lid Open: 23.5"
	SG2LG (721375)	Double, grooved surface. Work surface per side: 7.25" W x 9" D 240V / 3.2 kW / 13A / 1 Ph NEMA 6-20P line cord included.	22" x 22.75" x 15.5" Height with Lid Open: 23.5"
	SG2LF (721425)	Double, flat surface. Work surface per side: 7.25" W x 9" D 240V / 3.2 kW / 13A / 1 Ph NEMA 6-20P line cord included.	22" x 22.75" x 15.5" Height with Lid Open: 23.5"

PANINI GRILLS

Cecilware®
PRO

Medium Duty Sandwich or Panini Grills

Larger Grilling Surface



Grill sandwiches, chicken, hot dogs, and other foods to perfection!

A cast iron griddle surface on the top and bottom for even heating, and your choice of flat or grooved plates are covered with non-stick enamel for easy use.

The upper plate is adjustable to accommodate a wide variety of sandwiches and foods. A removable stainless steel grease tray makes this unit incredibly easy to clean, and its low clearance and compact footprint let it fit on any countertop.

- Counter balanced top plate ensures even cooking temperature up to 570° F.
- Large work surface.
- Stainless steel body construction.



	MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	TSG1G (720100)	Single, grooved surface. Work surface: 14.5" W x 10" D 110V / 1.4 kW / 13A / 1 Ph NEMA 5-15P line cord included.	19.75" x 15" x 12.5"
	TSG1F (720150)	Single, flat surface. Work surface: 14.5" W x 10" D 110V / 1.4 kW / 13A / 1 Ph NEMA 5-15P line cord included.	19.75" x 15" x 12.5"
	TSG2G (720200)	Double, grooved surface. 19.75" W x 10" D 240V / 3.1 kW / 13A / 1 Ph NEMA 6-20P line cord included.	19.75" x 20.25" x 12.5"
	TSG2F (720250)	Double, flat surface. Work surface: 19.75" W x 10" D 240V / 3.1 kW / 13A / 1 Ph NEMA 6-20P line cord included.	19.75" x 20.25" x 12.5"

WARMING & COOLING EQUIPMENT



WARMING EQUIPMENT




Syrup Warmers

Wonderful Hot Syrup

Everyone loves a hot breakfast of fresh pancakes, waffles, or French toast. But the best part is always the sweet, hot, flowing syrup.

These heated syrup dispensers hold 1 or 2 gallons of heated syrup at a constant temperature of 125 degrees Fahrenheit. At this temperature, syrup will stay thick and warm, but won't crystallize. Stable and durable stainless steel body with secure faucets that will prevent sticky drips on your countertops.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	SD1 (437100L)	1 gallon capacity, Tomlinson all-plastic self-closing faucet.	12.5" x 7.25"
SD2 (437200L)		2 gallon capacity, Tomlinson-S no-drip faucet	17" x 11.75"

COOLING EQUIPMENT

Cecilware[®]
PRO



Countertop Refrigerators

Compact and Chilly

Countertop display refrigerators allow you to put your food and beverages on display and increase impulse sales! These refrigerated merchandisers have double pane thermal glass doors with a built-in door locks and a strong magnetic gasket for exceptional energy efficiency.

- Interior lights show off your product.
- ETL and ETL sanitation listed.
- Adjustable thermostat between 34 - 45° F.
- Adjustable PVC coated wire shelves.



MODEL		DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
	CTR2.68LD (810115L)	Black, 2.7 cubic feet, (4) shelves, Includes lighted display header. 120V / 0.24 kW / 2A / 1 Ph NEMA 5-15P line cord included. Compressor: 1/8 hp	36.5" x 18" x 18.5"
	CTR3.75 (810105L)	Black, 3.8 cubic feet, (5) shelves. 120V / 0.24 kW / 2A / 1 Ph NEMA 5-15P line cord included. Compressor: 1/8 hp	33.75" x 19" x 18.75"

Optional Shelf for CTR3.75

MODEL	DESCRIPTION	PRODUCT DIMENSIONS (h x w x d)
08727L	Additional shelf for CTR3.75	15.75" W x 13" D

HELPFUL INFORMATION



PLANNED MAINTENANCE

Requirements & Frequencies

CATEGORY 1:

Care and Use Per Frequency Specified in Operators Manual

- Coffee Grinders
- Coffee Brewers (except RC400)
- Hot Water Dispensers
- Cooking Equipment
- UNIC Espresso Equipment

CATEGORY 2:

Onsite Planned Maintenance

Recommended to be scheduled and completed within 30 days of one-year anniversary of purchase.
To schedule, contact your local Authorized Service Agent.

- Urns and Hot Water Heaters

PLANNED MAINTENANCE

Requirements & Frequencies

CATEGORY 3:

One Year Planned Maintenance Schedule

Series	Model	Planned Maintenance Kit Part Number
Espresso Machines		
Super Automatic Espresso	Korinto Prime (1005-003)	250-00139
Orange Juice Machines		
Countertop Orange Juice	JX15MC (095500L)	250-00168
Floor Model Orange Juice	JX45AF (095555L)	250-00169
Frozen Granita Dispensers		
I-Pro 2 Bowl	I-PRO 2M light panel (1206-001), I-PRO 2E (1206-002)	250-00301
I-Pro 3 Bowl	I-PRO 3M (1206-004), I-PRO 3M light panel (1206-005) I-PRO 3E (1206-006) I-PRO 3E light panel (1206-007)	250-00302
Frosty Series 2 Bowl	Frosty 2 (1206-010)	250-00305
Frosty Series 3 Bowl	Frosty 3 (1206-011)	250-00306
MP Series Single Bowl Barrel Freezer	MP (1207-000)	250-00310
Frozen Desserts & Cold Cream Dispensers		
	GT Push 1 (1206-012)	250-00307
	GT Push 2 (1206-013)	250-00308
Ice Cream Dispensers		
	K-Soft (1208-000)	250-00311
	Karma Gravity (1208-002)	250-00312
Heated Dispensers		
	Lola 6 (2505-001)	250-00309

PLANNED MAINTENANCE

Requirements & Frequencies

CATEGORY 4:

Six Months Planned Maintenance Schedule

Series	Model	Planned Maintenance Kit Part Number
Cold Beverage Dispensers		
Simplicity Bubbler Mini Twin	CS-2E-16	250-00120
Simplicity Bubbler Mini Quad	CS-4E-16	250-00122
Simplicity Bubbler Triple Combo	CS-3D-16	250-00128
Simplicity Bubbler Single Standard	CS-1D-16	250-00124
Simplicity Bubbler Twin Standard	CS-2D-16	250-00126
Simplicity Bubbler Triple Tall	CS-3L-16	250-00130
Classic Bubbler Standard	D15-3	250-00136
Classic Bubbler Standard	D15-4	250-00136
Classic Bubbler Standard	D25-3	250-00138
Classic Bubbler Standard	D25-4	250-00138
Classic Bubbler Standard	D35-3	250-00140
Classic Bubbler Standard	D35-4	250-00140

PLANNED MAINTENANCE

Requirements & Frequencies

CATEGORY 4:

Six Months Planned Maintenance Schedule

Series	Model	Planned Maintenance Kit Part Number
Powdered Beverage Dispensers		
PIC 3 Flavor	PIC3 (61005D) PIC33A (61052D)	250-00012
PIC 5 Flavor	PIC5 (62933)	250-00113
GB 1 Flavor	GB1HC-CP (08003QL)	250-00105
GB 2 Flavor	GB2HC-CP (08003TL) 2K-GB-LD (080022L)	250-00106
GB 4 Flavor	4K-GB-LD (080041L)	250-00108
GB 6 Flavor	GB6M10-LD-U (080152L)	250-00110
GB 8 Flavor	GB8MP-10-LD-U (080167L)	250-00111
Cold Beverage Dispensers		
Classic Bubblers Mini	E29-3	250-00142
Classic Bubblers Mini	E29-4	250-00142
Classic Bubblers Mini	E49-3	250-00144
Classic Bubblers Mini	E49-4	250-00144
G-Cool Single	C-1S-16 (231-00162)	250-00132
G-Cool Double	C-2D-16 (231-00166)	250-00133
G-Cool Focus Flavor Triple	C-3D-16 (231-00168)	250-00134
G-Cool Mini-Duo	C-2S-16 (231-00164)	250-00133
G-Cool Mini-Quattro	C-4D-16 (231-00170)	250-00135
Frozen Beverage and Dessert Dispensers		
3000 Barrel Mechanical Freezer	3312 (CFB3312-A)	250-00116
5000 Barrel Electronic Freezer	5711 (CFB5711-B)	250-00119

PRODUCT CERTIFICATIONS

Domestic Certifications

Grindmaster strives to design, create, and deliver the highest quality beverage and cooking equipment to help you build your business. Sanitation, safety, quality, and public health are critical. That is why Grindmaster works with numerous independent, third-party testing and certification organizations to simplify your search for superior equipment. Below are the certifications and marks that we refer to in this catalog, along with a brief description of the standards used to provide certification.

UL

Underwriters Laboratories (UL) is an independent, not-for-profit, nongovernmental organization that has been testing products for public safety for more than a century and has developed more than 1,000 safety standards. UL serves a wide range of customers including manufacturers, retailers, consumers, and regulating bodies.



UL Certification

The UL Certification symbol can be found on products in compliance with UL's safety standards and U.S. safety requirements.



C-UL US Certification

The C-UL US Mark indicates that a product meets the testing standards for UL listing, as well as applicable regulations on that type of product in the United States and Canada. The Canada/US UL mark is optional, but UL encourages those manufacturers with products certified for both countries to use this new, combined mark.

ETL

ETL is the certification mark used by Intertek, a Nationally Recognized Testing Laboratory (NRTL) providing independent evaluation, testing, and certification of any electrically operated or gas- and oil-fired product. A product bearing the ETL listed mark is determined to have met the minimum requirements of prescribed product safety standards. Moreover, the mark indicates that the manufacturer's production site conforms to a range of compliance measures and is subject to periodic follow-up inspections to verify continued conformance. The ETL listed mark is the equivalent of the UL listed and CSA listed marks throughout the United States and Canada.



Intertek

ETL Sanitation Certification

The ETL Sanitation Mark indicates a product meets applicable requirements for food safety. To achieve it, the item must pass tests by ANSI/NSF standards and the certification shows production conforms to compliance measures for ensuring a food-safe product. Facilities are inspected on a regular basis to verify those standards continue to be met. The ETL Certification with "sanitation listed" inscribed on the bottom of the circle signifies that the product has been tested and deemed compliant with product safety standards.



Intertek

ETL Certification - United States

A product bearing the ETL Certification with the U.S. mark has been tested and deemed compliant with U.S. product safety standards.



Intertek

ETL Certification

An ETL Certification Mark signifies that the product complies with both U.S. and Canadian product safety standards.

PRODUCT CERTIFICATIONS

Domestic Certifications

NSF

NSF (National Sanitation Foundation) International is the only third-party testing organization to undertake a complete evaluation of every aspect of a product's development for public health and safety, quality, and sanitation. NSF food equipment standards include requirements for material safety, to ensure the product will not leach harmful chemicals into food; design and construction, to ensure the product is cleanable and is not likely to harbor bacteria; and product performance. As part of the certification process, the production facility is subject to unannounced plant inspections.



NSF Certification

The NSF Certification Mark on a food equipment product confirms that NSF has assessed and certified its conformity with the relevant NSF/ANSI food safety standards. Products with the NSF Mark receive guaranteed regulatory acceptance in North America and improved acceptance worldwide.



ELECTRICAL

NSF Electrical Certification

The NSF Electrical Mark certifies electrical safety certification and compliance with U.S. requirements.



C US
ELECTRICAL

cNSFus Electrical Certification

NSF is accredited by OSHA as a nationally recognized testing laboratory to provide electrical safety certification to various UL standards in a wide range of foodservice equipment categories. The cNSFus Mark indicates compliance with both Canadian and U.S. requirements.

NSF-20

NSF-20 Certification

NSF International, in conjunction with ANSI has created the NSF / ANSI 20 certification. This establishes minimum food protection and sanitation requirements for the materials, design, fabrication, construction, and performance of commercial bulk milk dispensers and their related components. This includes equipment designed to dispense servings of milk or milk products by manual or machine actuation. This standard does not apply to dispensing freezers (soft-serve machines), vending machines, or manual food and beverage dispensing equipment covered by the scope of other NSF standards.

The American National Standards Institute (ANSI) is a private non-profit organization that oversees the development of voluntary consensus standards for products, services, processes, systems, and personnel in the United States.

PRODUCT CERTIFICATIONS

Domestic Certifications

CSA

CSA (Canadian Standards Association) International is an independent, not-for-profit member-based association that tests products for compliance with national and international safety and performance standards. CSA Group is recognized and accredited in the U.S. by OSHA, which enables them to use the U.S. standards written or administered by organizations including ANSI, UL, and NSF, among others.



CSA Certification

The CSA Mark signifies that the product meets applicable U.S. and Canadian standards, including those from CSA, CSA America, ANSI, ASME, ASSE, ASTM, NSF, and UL. If a product has features from more than one area (such as electrical equipment with fuel-burning features), the mark indicates compliance with all applicable standards.



CSA Star Certification Mark

Indicates that the product was tested and has met the certification requirements for gas-fired products in the United States.



CSA Flame Certification Mark

Indicates that the product was tested and has met the certification requirements for gas-fired products in Canada.

GRINDMASTER UNIC Crathco

www.grindmaster.com

4003 Collins Lane
Louisville, KY 40245
USA

Phone: 502.425.4776
Toll Free: 800.695.4500
Fax: 502.425.4664

Form # **PR-025-16**
Item # **390-00290**

© Grindmaster Corporation 2021. Printed in USA